

XF40-Q1765 Explosion-Protected Network Camera

Fixed camera for hazardous areas

XF40-Q1765 Explosion-Protected Network Camera is suitable for onshore, offshore, marine and heavy industrial environments. It features a 316L stainless steel housing certified for hazardous areas according to for example ATEX, IECEx and UL. The housing prevents any inside sparks or explosions from escaping and igniting vapors, gases, dust or fibers in the surrounding air. XF40-Q1765 provides superb image quality and color fidelity and a high level of flexible integration with other equipment, such as access control and fire alarms. It offers flexible remote accessibility, using any existing IP-based networks.

- > **Stainless steel (SAE 316L) and impact resistance**
- > **Full HDTV 1080p resolution**
- > **18x zoom and autofocus**
- > **Wide temperature range**



XF40-Q1765 Explosion-Protected Network Camera

Models	XF40-Q1765 XF40-Q1765 -60 C XF40-Q1765 -50 C UL All models are available in different versions depending on the regional requirements for hazardous equipment certification.	Germanium protective window
Certification part code	XF40-Q1765/XF40-Q1765 -60 C: 1410-15-00 All models delivered in 1410 series explosion-protected housing. XF40-Q1765 -50 C UL: OXALIS-UL1410-15	Memory 256 MB RAM, 128 MB Flash
Camera		Power Max consumption, 24 V AC: 28 W
Image sensor	Progressive scan RGB CMOS 1/2.9"	Connectors XF40-Q1765 models: Three M20 conduit entries XF40-Q1765 UL models: Three 3/4" NPT conduit entries
Lens	4.7–84.6 mm, F1.6–2.8 Horizontal field of view 59°–4° Vertical field of view 35°–2° Autofocus	Storage Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see www.axis.com
Day and night	Automatically removable infrared-cut filter	Operating conditions XF40-Q1765: -40 °C to 60 °C (-40 °F to 140 °F) XF40-Q1765 -60 C: -60 °C to 40 °C (-76 °F to 104 °F) XF40-Q1765 -50 C UL: -50 °C to 60 °C (-58 °F to 140 °F) Humidity 10–100% RH (condensing)
Minimum illumination	Color: 0.5 lux at 30 IRE F1.6 B/W: 0.04 lux at 30 IRE F1.6	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Shutter time	1/28000 s to 2 s	Approvals EMC EN 55022 Class A, EN 55024 Class A, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, RCM AS/NZS CISPR 22 Class A Safety EN/UL/CSA 60065 Environment IEC/EN 60529 IP66, IEC/EN 62262 IK10 body, IK08 glass Explosion IEC/EN/UL/SANS/CSA 60079-0, IEC/EN/UL/SANS/CSA 60079-1, UL1203 CSA C22.2 No. 25 M 1966, CSA C22.2 No. 30 M 1986
Pan/Tilt/Zoom	18x optical zoom and 12x digital zoom, total 216x zoom 64 preset positions	Certifications ATEX: II 2 G Ex d op pr IIC T4 II 2 D Ex tb IIIC T135°C Db IP66/67 IECEX: Ex d IIC T4 -60°C ≤ Ta ≤ +60°C Gb Ex tb IIIC T135°C Db IP66/67 Imetro: Ex d IIC T4 -60°C ≤ Ta ≤ +60°C Gb Ex tb IIIC T135°C Db IP66/67 LCus C1/Z1: Class 1 Zone 1 AEx d IIC T4 Gb -60°C ≤ Ta ≤ +60°C cLCus C1/D1: Class I, Division 1, Groups B, C, D, -60°C ≤ Ta ≤ +60°C / Class II, Division 1, Groups E, F, G, IP66/IP67 cLC CSA: Ex d IIC T4 -60°C ≤ Ta ≤ +60°C EAC: Ex d IIC -60°C ≤ Ta ≤ +60°C Gb Ex tb IIIC T135°C Db, IP66/67 CCOE: Ex d IIC -60°C ≤ Ta ≤ +60°C Gb Ex tb IIIC T135°C Db, IP66/67 CNEX: Ex d IIC T4 Gb Ex tb IIIC 135°C Db, IP66/67 Certex: II 2 G Ex d op pr IIC T4 II 2 D Ex tb IIIC T135°C Db IP66/67 UL: Class I, Division 1, Groups B, C, D, T4+, Class II, Division 1, Groups E, F, G IClass 1 Zone 1 A Ex d IIB + Hydrogen T4 -50°C ≤ Ta ≤ +60°C
Video		Dimensions 165 x 176 x 480 mm (6 1/2 x 6 15/16 x 18 7/8 in)
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, and Main profiles Motion JPEG	Weight 14 kg (31 lb)
Resolutions	1920x1080 HDTV 1080p to 160x90	Included accessories Sunshield, installation guide, Windows decoder 1-user license, AXIS Surveillance microSDXC™ Card 64 GB
Frame rate	Up to 30/25 fps (60/50 Hz) in all resolutions	Optional accessories Ex Washer Tank Pressurized ATEX/IECEX, Ex Power Supply UL, Ex Power Supply ATEX/IECEX, Ex Cable ATEX/IECEX/EAC in various lengths, explosion-protected mounts All accessories are not available for all certifications. For more accessories, see www.axis.com
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth VBR/CBR H.264	Video management software AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
Image settings	Compression, color, brightness, sharpness, white balance, exposure control, exposure zones, backlight compensation, WDR – dynamic contrast, fine tuning of behavior at low light, rotation, text and image overlay, day/night shift level	Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Network		Warranty Axis 3-year warranty, see www.axis.com/warranty
Security	Password protection, IP address filtering, HTTPS ^a encryption, Digest authentication, User access log, Centralized Certificate Management	
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at www.onvif.org	
Analytics	AXIS Video Motion Detection 4, active tampering alarm Support for AXIS Camera Application Platform enabling installation of third-party applications, see www.axis.com/acap	
Event triggers	Analytics, Edge storage events	
Event actions	Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap File upload via FTP, SFTP, HTTP, HTTPS network share and email Notification via email, HTTP, HTTPS and TCP	
Data streaming	Event data	
Built-in installation aids	Pixel counter	
General		
Casing	IP66-, IP67- and IP69-rated, IK10 impact-resistant, electro-polished SAE 316L stainless steel casing for maximum corrosion protection	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:
www.axis.com/environmental-responsibility