

DIGITUS USB Type-C™ Adapter, USB A - USB-C™

AK-300524-000-S
EAN 4016032467410



USB Type-C adapter, type A to C M/F, 3A, 5GB, 3.0 Version, bl

The DIGITUS® USB Type A to USB-C™ adapter allows you to use your current USB Type-C™ devices on an older USB A port. The adapter supports the USB 3.0 specification with data transfers of up to 5Gbps and provides a maximum power of 15 W (3 A). By simply flipping the USB-C™ connector, you can switch between USB 3.0 and USB 2.0 speeds if supported by the USB A connector. The integrated 56k pull-up resistor protects your devices from damage due to overload and supplies only as much power as the connected USB-C™ device needs. With this adapter you can use the full range of previous USB versions, backward compatible to the USB 2.0 / 1.1 standards.

Connect USB-C™ devices to an USB A port - Keep using your devices with USB A port

- Adapter: From USB A to USB-C™ (Use USB-C™ devices on USB A ports)
- SuperSpeed data transfer: 5 Gbit/s (USB 3.0 if supported by USB A)
- Power supply USB-C™: 3A max (15 W)
- USB Type-C™ plug: can be used on both sides, reverse polarity protected

- Integrated pull-up resistor 56k to protect your source devices (Notebook, PC)
- Abwärtskompatibel zu USB 2.0 / 1.1
- Operating temperature: -15 ~ 50°C
- Operating humidity: -25 - 80% RH (non-condensing)
- Storage temperature: -20 ~ 60°C
- Storage humidity: 20% - 85% RH (non-condensing)
- Material housing: aluminium
- Color: Black
- Connector surface: nickel-plated
- Color cable: black
- USB-C Products: yes
- Connector 1: USB A, plug
- Connector 2: USB-C jack
- USB compliance: USB Type-C™

Package contents

- 1 x USB Type-C™ adapter, USB A - USB-C™
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	9.00	26.00	38.00	24.00	23,712.00
Packaging Unit Inside	10	0.09	3.00	20.00	25.00	1,500.00
Packaging Unit Single	1	0.01	0.70	9.00	20.00	126.00
Net single without Packaging	1	0.01	0.70	9.00	20.00	126.00

More images:

