

Qty. Description

1 UNILIFT KP350-A-1

**Note! Product picture may differ from actual product**Product No.: [013N1600](#)

Submersible drainage pump

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.

The pump is fitted with suction strainer and a carrying handle and is supplied with a 5 m mains cable and float switch for automatic start and stop.

The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.

The pump has a double shaft seal consisting of two lip seals with grease in-between.

The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid.

The motor is filled with a non-toxic motor liquid.

Liquid:
Liquid temperature range: 0 .. 40 °C
Density: 998.2 kg/m³

Technical:
Maximum flow: 3.89 l/s
Max. Particle: 10 mm

Materials:
Pump housing: Stainless steel
EN 1.4301
AISI 304
Impeller: Stainless steel
EN 1.4301
AISI 304

Installation:
Range of ambient temperature: 0 .. 50 °C
Type of connection: Rp
Size of connection: 1 1/4 inch
Maximum installation depth: 2 m

Electrical data:
Power input - P1: 720 W

Qty.	Description																														
	<table> <tr> <td>Mains frequency:</td> <td>50 Hz</td> </tr> <tr> <td>Rated voltage [V]:</td> <td>1 x 220-240 V</td> </tr> <tr> <td>Rated current:</td> <td>3.2 A</td> </tr> <tr> <td>Capacitor size - run:</td> <td>10 µF/400 V</td> </tr> <tr> <td>Enclosure class (IEC 34-5):</td> <td>IP68</td> </tr> <tr> <td>Insulation class (IEC 85):</td> <td>F</td> </tr> <tr> <td>Length of power cable:</td> <td>5 m</td> </tr> <tr> <td>Type of cable plug:</td> <td>SCHUKO</td> </tr> <tr> <td colspan="2">Others:</td> </tr> <tr> <td>Net weight:</td> <td>7.2 kg</td> </tr> <tr> <td>Gross weight:</td> <td>7.6 kg</td> </tr> <tr> <td>Shipping volume:</td> <td>0.013 m³</td> </tr> <tr> <td>Danish VVS No.:</td> <td>391215035</td> </tr> <tr> <td>Country of origin:</td> <td>HU</td> </tr> <tr> <td>Custom tariff no.:</td> <td>84137021</td> </tr> </table>	Mains frequency:	50 Hz	Rated voltage [V]:	1 x 220-240 V	Rated current:	3.2 A	Capacitor size - run:	10 µF/400 V	Enclosure class (IEC 34-5):	IP68	Insulation class (IEC 85):	F	Length of power cable:	5 m	Type of cable plug:	SCHUKO	Others:		Net weight:	7.2 kg	Gross weight:	7.6 kg	Shipping volume:	0.013 m ³	Danish VVS No.:	391215035	Country of origin:	HU	Custom tariff no.:	84137021
Mains frequency:	50 Hz																														
Rated voltage [V]:	1 x 220-240 V																														
Rated current:	3.2 A																														
Capacitor size - run:	10 µF/400 V																														
Enclosure class (IEC 34-5):	IP68																														
Insulation class (IEC 85):	F																														
Length of power cable:	5 m																														
Type of cable plug:	SCHUKO																														
Others:																															
Net weight:	7.2 kg																														
Gross weight:	7.6 kg																														
Shipping volume:	0.013 m ³																														
Danish VVS No.:	391215035																														
Country of origin:	HU																														
Custom tariff no.:	84137021																														

Description	Value
General information:	
Product name:	UNILIFT KP350-A-1
Product No:	013N1600
EAN number:	5700393433137
Technical:	
Maximum flow:	3.89 l/s
Maximum head:	9 m
Max. Particle:	10 mm
Model:	A
Materials:	
Pump housing:	Stainless steel
Pump housing:	EN 1.4301
Pump housing:	AISI 304
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
Installation:	
Range of ambient temperature:	0 .. 50 °C
Type of connection:	Rp
Size of connection:	1 1/4 inch
Maximum installation depth:	2 m
Liquid:	
Liquid temperature range:	0 .. 40 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input - P1:	720 W
Mains frequency:	50 Hz
Rated voltage [V]:	1 x 220-240 V
Rated current:	3.2 A
Capacitor size - run:	10 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Thermal protec:	internal
Length of power cable:	5 m
Type of cable plug:	SCHUKO
Controls:	
Level switch:	float switch
Others:	
Net weight:	7.2 kg
Gross weight:	7.6 kg
Shipping volume:	0.013 m ³
Danish VVS No.:	391215035
Country of origin:	HU
Custom tariff no.:	84137021

