© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

System 106 Keyless In fingerprint module



Specification	Order No.	Packing unit	PS	EAN
stainless steel	5551 920	1	20	4010337072799
aluminium	5551 926	1	20	4010337072805
traffic white (laquered)	5551 902	1	20	4010337072812
stainless steel V4A	5551 914	1	20	4010337112860
bronze	5551 921	1	20	4010337108252

Features

- Fingerprint module as professional biometric access control system based on the new generation of surface-scan technology.
- Start-up and administration via app.
- Use as a stand-alone device with Gira DCS switching actuators or in combination with the Gira door communication system as a door call system for buildings with several residential units.
- Scanning the deepest layer of skin using high frequency. High detection rate and security against tampering.
- An evaluation of the unique characteristic features of the living human finger.
- Up to 99 fingers can be managed by the fingerprint reader.
- Reliable detection of fingers which, for example, were slightly injured during gardening (only the top layer of skin was injured).
- Data protection through the use of encryption.
- Quick response time from fingerprint scan to enabling:
  up to 30 saved fingers – approx. 1 s,
  up to 99 saved fingers – approx. 3 s.
- Night design of the fingerprint surface for orientation using white LED illumination.

Illustrations are similar and may deviate from originals.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

- 360° fingerprint readability.
- Three-colour LED status display for visual signalling during programming and operation.
- Master PIN number provided on included sealed safety card if Administrator finger is no longer available. The device can be reset at the factory with the accompanying safety card.
- Acknowledgement buzzer for acoustic signalling for user or installer.
- Audible warning in case of unauthorised removal of the fingerprint top unit, i.e. tamper detection. Tampering circuit with switching actuator in the door communication system.

Inputs and outputs

- Connection cable connector strip for the Gira door communication system.

Technical data

Power supply	
- System:	Flat ribbon cable, 10-pole
- 2-wire bus:	via control device or via AS (DC 24 V 300 mA)
Power consumption	
- Maximum:	1 W
- Stand-by mode:	700 mW with lighting
Relay	
- Load capacity:	AC/DC 24 V / 1.6 A
Connections	
- 2-wire bus:	1 x plug terminal
- Additional power supply:	1 x plug terminal
- System:	2 x connector strip
Resistance to EMD:	Approx. 15 kV
Protection class:	IP54
Ambient temperature:	-25 °C to +70 °C

:
:

Notes

- Keyless In devices can be connected to the Gira HomeServer using the DCS-IP gateway. This enables intelligent links. In this way, e.g. temporary or one-time access authorisation can be easily granted. All data including access authorisations can be managed centrally and flexibly using the Gira HomeServer.
- Children s fingers can generally first be reliably detected from 6 years of age.
