



Delock WLAN 802.11 ac/a/b/g/n Antenna RP-SMA plug 5 ~ 7 dBi directional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals. Due to the directivity of this antenna the wireless supply is improved in rooms.



Specification

- Connector: RP-SMA plug
- Frequency range:
2.400 - 2.500 GHz
5.100 - 5.875 GHz
- Antenna gain:
5 dBi @ 2.5 GHz
7 dBi @ 5.7 GHz
- Impedance: 50 Ohm
- Polarisation: vertical
- VSWR: 2.0
- HBW horizontal beamwidth:
70° @ 2.5 GHz
50° @ 5.7 GHz
- VBW vertical beamwidth:
70° @ 2.5 GHz
60° @ 5.7 GHz
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS UV resistant
- Colour: black
- Dimensions:
ca. 90 x 120 x 13 mm (with tilt joint)
ca. 90 x 95 x 13 mm (without tilt joint)
- Diameter:
ca. 7.80 mm (top)
ca. 12.90 mm (RP-SMA)

System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna




Item No. 88447

EAN: 4043619884476

Country of origin: Taiwan, Republic of China

Package: Poly bag

Images





Interface	
connector:	RP-SMA plug
Technical characteristics	
Frequency range:	2.400 - 2.500 GHz
	5.100 - 5.875 GHz
Gain:	5 dBi @ 2.5 GHz
	7 dBi @ 5.7 GHz
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	vertical
VSWR:	2.0
Physical characteristics	
Housing material:	ABS UV protected
Colour:	black