

Wallbox

Wallbox Pure Polar 7m



Wallbox Pure Polar 7m

Wallbox

Productnumber: 59141701

Dimensions: 293 x 293 x 110 mm

Wallbox - for fast and safe charging of private e-vehicles, charging power up to 11 kW (3-phase)/3.7 kW (1-phase) and a maximum charging current of 16 A, variably adjustable charging power, integrated DC fault current detection for DC residual currents of ≥ 6 mA and temperature monitoring for a safe charging process, stylish design and compact enclosure dimensions for wall and pedestal mounting, protection class IP54, maximum connection cross-section of supply terminal 6 mm², shock resistance IK08, protection class II.

Simple installation and fast configuration with the free-of-charge Spelsberg Wallbox App (available for iOS, Version 14 and higher, and Android Version 6 and higher), contactless authorisation of the charging process by RFID, LED and audible signals for clear feedback on status changes.

Polar, connected 7 m charging cable with Type 2 charging plug



Stylish, minimalist design meets smart charging technology - for high power in its most attractive form. Optimum dimensions with a low depth of 110 mm emphasise the timeless design with a simultaneous focus on fast and easy installation.

Say goodbye to laborious adjustments of rotary and dip switches with the Spelsberg wallbox: The intelligent app allows full configuration and control through the convenience of a Smartphone.

Technical Data

electrical characteristics

max. charging power:	11 kW
max. charging current:	16 Ampere
Variably adjustable charging current:	yes
System side connection:	3-phase

electrical characteristics

Rated operating voltage AC:	400 V
Nominal frequency:	50 Hz
Charging mode (IEC 61851):	3 C
Long charging cable:	7 m
Connector plug:	Type 2
Temperature monitoring:	Charging current reduction

DC fault current detection ≥ 6 mA:

yes

Load switch:	Contacteur, 4-pole
Max. conductor cross section:	6 mm ²
Min. conductor cross section:	0,2 mm ²
Protection class:	II
Degree of pollution:	3
Type of protection:	IP54
vented:	no

Colours

Base unit colour:	white
Cover colour:	Polar

Additional features

Mobile app:	Yes
Access control/Authorisation:	RFID
Status display:	LED
Audible status feedback:	yes
Load management:	none
Integrated MID meter:	no
Excess PV charging:	no
Plug & Charge (ISO 15118):	no
Auto Charge:	no
Firmware Updates:	USB
Inlet for data cable:	No
Eligibility:	no

Dimensions

Width:	293 mm
Length:	293 mm
Height:	110 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	no
Halogen free:	yes
Glow-wire flammability according to EN 60695-2-11:	650 °C
Weight (excluding charging cable):	2.5 kg

mechanical properties

Type of fastening:	Wall/pedestal mounting
Impact strength:	IK08
Sealable:	no
Type of top part:	Cover

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C
Set-up location:	Indoors / sheltered outdoors

Material

Base unit material:	Polycarbonate, glass-fibre reinforced
Cover material:	Polycarbonate

Accessories

[59181501 - WB WSD - Weather-proof cover for wallbox](#)

[59181301 - RFID-C Polar - RFID chip](#)

[59180601 - AP-SF2 - Pedestal adapter plate](#)

[59180501 - SF WSD - Weather-proof cover for pedestal](#)

[59180101 - SF1 - Wallbox pedestal](#)

[59180701 - SH Polar - Connector holder](#)

[59180201 - SF1 WSD - Wallbox pedestal](#)

[59180301 - SF2 - Wallbox pedestal](#)

[59181101 - DC Polar - Wallbox design cover](#)

[59180401 - SF2 WSD - Wallbox pedestal](#)

[59181001 - LL 7m T2 - Charging cable](#)

Cable gland

