



NEW

Room temperature controller with CO₂/moisture sensor and

Functions at a glance

- Control element with room temperature controller function and CO₂/moisture sensor.
- With integrated KNX bus coupler.
- With labelling field.
- Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green.
- Push switch function: switching / dimming / blind / sending values / scenes etc.
- For activating heating, ventilation and fan coil actuators.
- Master/slave configuration.
- With base-load operation.
- The fan stage can be switched manually or in automatic mode.
- Class of temperature controller 1
- Contribution to space heating energy efficiency 1,0%.
- Number of bus subscribers: 2
- Control element: rocker switch left/right
- Display elements: Display of operating mode, temperature, fan coil level, humidity value, CO₂ value, time or date via LCD
- Protection class (device): IP 20
- Temperature range (device): -5 °C - 45 °C
- Storage temperature range: -25 °C - 55 °C
- Transport temperature range: -25 °C - 70 °C
- Dimensions: (L x W x D): 117.1 mm x 90.1 mm x 13.5 mm
- As required, you can find the programmable functions in the current application description, which you can download in the Support Centre on our Internet page.
- For compatible lettering software, visit www.BUSCH-JAEGER-labelingtool.com.

Order details

Article No.:	SBC/U6.0.11-83
Order No.:	2CKA006330A0059
EAN:	4011395298930
Customs tariff number:	90321020
Price group:	42
Price:	394,00 EUR plus VAT

Downloads

Instruction manual

- » [Installation and operating instructions](#)
- » [Product manual](#)

Certificates

- » [EU-declaration of conformity](#)

Software

- » [ETS4/ETS5 application , V 1.2, 22.02.2022](#)
- » [Release Notes , 22.02.2022](#)