



Line Amplifier 9Z2

Amplifier for signal gain for 2 orbital positions

EAN	Colour	Item no.	Weight (Box)	Weight	Box	Device (W x H x D)
4019588232310	silver/yellow	0002/3231	280 g	190 g	25.20 x 7.40 x 4.70 cm	20.80 x 5.50 x 3.20 cm

LNB CONTROL Current consumption: max. 850 mA Ambient temperature: -25 ... 55 °C	Top features: Optionale Stromversorgung über Steckernetzteil Top features: Gleiches Rastermass der F-Buchsen wie GigaSwitch 9/8 und TechniRouter 9/8	TECHNICAL DATA Satellite inputs: 8 Terrestrial input: 1
AMPLIFICATION Sat: 15 ... 20 dB fest, schräglagenentzerrt Terrestrial: 7 ... 14 dB einstellbar Return path: -1 dB	POWER CONSUMPTION In operation: 5.5 W	SCOPE OF DELIVERY Line Amplifier 9Z2, instruction manual
DECOUPLING Trunks: 50 dB	POWER SUPPLY Nominal voltage: 15 V DC Mains adapter: external (Optional)	
GENERAL CHARACTERISTICS Top features: Kompensiert die Dämpfung von bis zu 60 m Koaxkabel Top features: Rückkanaltauglich von 2...68 MHz	RECEPTION RANGE Sat: 950 ... 2150 MHz Terrestrial: 87 ... 790 MHz Return path: 2 ... 68 MHz	

KEYFEATURES	
Multiple subscribers	2 orbit positions