

Product Specifications

WRX560



Hardware Specs

CPU

Quad core 1.4 GHz

Hardware Acceleration Engine

Layer 4 / Layer 7

Memory

512 MB DDR4

Antenna Type

- 4×4 MIMO high-performance internal antenna (5 GHz)
- 2×2 MIMO high-performance internal antenna (2.4 GHz)

LAN Port

- 2.5GbE (RJ-45) x 1
- Gigabit (RJ-45) x 3

WAN Port

- Gigabit (RJ-45) x 1
- 2.5 GbE (RJ-45) x 1 (Dual WAN)

External Ports

USB 3.2 Gen 1 x 1 (5V, 0.9A power output)

IEEE 802.11ax

- IEEE 802.11a/b/g/n/ac/ax
- 2.4GHz: 600Mbps
- 5GHz: 2400Mbps
- Simultaneous dual-band Wi-Fi

Wi-Fi Encryption

WPA/WPA2-Personal, WPA/WPA2-Enterprise, WPA2/WPA3-Personal, WPA3-Personal/Enterprise, Wi-Fi Enhanced Open (OWE)

Button and Switch

WPS, Power, Reset, Wi-Fi On/Off

Size (Height x Width x Depth)

233 mm x 194 mm x 66 mm

Weight

1.35 kg

Temperature

Operating Temperature	5°C to 40°C (40°F to 104°F)
-----------------------	-----------------------------

Storage Temperature	-20°C to 60°C (-5°F to 140°F)
---------------------	-------------------------------

Relative Humidity	5% to 95% RH
-------------------	--------------

Certification

- FCC
- UKCA
- CE
- BSMI
- VCCI
- RCM
- KC
- iDA
- TELEC
- JATE
- IC

Wi-Fi Certification

- CE
- UKCA
- FCC
- NCC
- RCM
- iDA
- TELEC
- KC
- IC

Warranty

2 Years

Notes

The warranty period starts from the purchase date as stated on your purchase receipt. [\(Learn more\)](#) Synology will provide software updates until Dec 2027, and extended support may be provided.

AC Input Power Voltage

100 V to 240 V AC

Power Frequency

50/60 Hz, Single Phase

Power Consumption*

10.80 W (Access)

7.94 W (Idle)

Environment

RoHS Compliant

Packaging Content

- Main Unit X 1
- AC Power Adapter X 1
- RJ-45 LAN Cable X 1
- Quick Installation Guide X 1

Software Specs

SRM Specifications

Wireless

Wi-Fi MAC Address Filter

v

Maximum MAC Filters

64

Maximum devices on per MAC filter	256
Seamless Roaming	802.11k/v/r standard support
Beamforming	v
DFS	v
WDS	v
Maximum Number of Wi-Fi SSID	10
Schedulable Wi-Fi	v
Guest Network	<ul style="list-style-type: none"> • Guest Portal • Customized page style • Connection time limit • Password Rotation
WPS 2.0 (Wi-Fi Protected Setup 2.0)	v
3G / 4G Dongle & Tethering (Learn more)	v
Maximum Connected Devices*	150
Primary Wi-Fi Point	v
Wi-Fi Point	v
Recommended Maximum Number of Wi-Fi Points	<ul style="list-style-type: none"> • 1 Primary + 6 Wi-Fi points (in all wireless uplink connection environment) • 1 Primary + 12 Wi-Fi points (in all wired uplink connection environment. Learn more)
Notes	<ul style="list-style-type: none"> • The numbers above are for reference only. Actual performance and behavior may depend on network environment and settings • WRX560 supports at least 150 connected devices concurrently transmitting data

Network

Internet Connection	<ul style="list-style-type: none">• Dynamic IP, Static IP, PPPoE, PPTP, DS-Lite (AFTR)• 3G/4G LTE dongle• Android Tethering• iPhone Tethering
Operating Mode	<ul style="list-style-type: none">• Wireless Router• Wireless AP
DMZ	v
IPv6	IPv6 DHCP server/client, DS-Lite, 6in4, 6to4, 6rd, Dual-Stack, DHCPv6-PD, IPv6 Relay, FLET's IPv6
DHCP	Server/client mode, client list, MAC address reservation
Maximum DHCP Reservations	500
LAN / WLAN IGMP Snooping	v
Network Address Translation (NAT)	v
PPPoE relay	v
Policy route	v
Static route	v
Maximum IPv4 Static Routes	100
Maximum IPv6 Static Routes	100
Diagnosis Tools	<ul style="list-style-type: none">• Ping• Traceroute
NAT Loopback (Hairpinning)	v
VLAN	
Maximum Number of Network Segmentation	5
Trunk	v

Port Forwarding

Maximum Port Forwarding Rules	64
-------------------------------	----

Maximum UPnP Rules	64
--------------------	----

Port Triggering

Maximum Port Triggering Rules	32
-------------------------------	----

Minimum Port Triggering Timeout	30s
---------------------------------	-----

Maximum Port Triggering Timeout	3600s
---------------------------------	-------

VPN

- VPN server (WebVPN, SSL VPN, SSTP, OpenVPN, L2TP/IPSec, PPTP, Site-to-Site)
- VPN client (PPTP, OpenVPN, L2TP/IPSec)
- VPN Pass-through (PPTP, IPSec, L2TP)

Traffic Control

Internet Ban, Device Speed & Priority	v
---------------------------------------	---

Application Layer (L7) Quality of Service (QoS)	v
---	---

Maximum Device Rules	64
----------------------	----

Maximum Application Rules per Device	32
--------------------------------------	----

Traffic Monitor

Live View	v
-----------	---

Historical Statistics	Daily, Weekly, Monthly, Annual
-----------------------	--------------------------------

Website History	v
Application Detection	v
Traffic Report	
Country Auto Update	v
Schedulable	v
Traffic Analysis Period	Daily, Weekly, Monthly, Annual
Export Formats	.CSV, .HTML

Add-on Packages [view the complete package list](#)

Safe Access	
User Profile	15
Network Profile	5
Customized Internet Schedule	v
Time Quota	v
IPv4 / IPv6 DNS-based Web Filter	<ul style="list-style-type: none"> Schedule Database Request to unblock
Customized Allow / Block List	<ul style="list-style-type: none"> Maximum blocked URLs: 100 Maximum allowed URLs: 100
Pause Internet	v
Reward	v
Log	v
Report	v
Safe Search	Bing, Google, YouTube, Duckduckgo
Threat Intelligence Database	Support in IPv4 & IPv6

Google Safe Browsing	Support in IPv4 & IPv6
Database Auto Update	Threat Intelligence Database, Google Safe Browsing, DNS-based web filter

Threat Prevention

Greatly enhance the security of your router, designed to safeguard your network against internet threats

VPN Plus Server

Easily create and manage secure VPN access through a web browser or client. Supports various VPN services — Site-to-Site VPN, WebVPN, SSL VPN, Remote Desktop, SSTP, OpenVPN, L2TP over IPsec, and PPTP

Maximum Client VPN Access License	20
Site-to-Site VPN	v
Maximum Site-to-Site VPN Tunnels	10
Remote Desktop (RDP + VNC)	3
Connection List	v
Log	v
Report	v

DNS Server

Helps users find and translate domain names into IP addresses

Download Station

Supported download protocols: BT/HTTP/FTP/NZB/eMule

Maximum Concurrent Download Tasks	20
Maximum Concurrent BT Download Tasks	20

Media Server

- Media indexing
- DLNA Compliance

RADIUS Server

Provides centralized authentication, authorization, and accounting for wireless network access

Mobile Apps

Supported Mobile Apps

DS router (Android/iOS)	<ul style="list-style-type: none">• First Time Installation• Network overview• Wi-Fi management• Wi-Fi system topology• Safe Access• Traffic Control• Network security (firewall, port forwarding, Internet ban)• Wake on LAN• System Update
VPN Plus (Android/iOS)	v
DS get (Android)	v
DS file (Android/iOS)	v

Management

Operating System

Synology Router Manager (SRM)

Anywhere Access to SRM

Synology QuickConnect & Dynamic DNS (DDNS)

Security

Firewall/SPI Firewall, DoS Protection, VPN Pass-through (PPTP, IPSec, L2TP), Auto block, SSL certificate, Security Advisor, two-factor authentication

Wake on LAN (WOL)

WOL over QuickConnect	v
Maximum Connected Devices	100

Notification

Email, SMS, push service (via DS router)

Printer Server

Maximum printer: 1

Others

Free OS Upgrade	v
SSH	v
SNMP	v
Configuration Backup & Restore	v
User Account Management	v

USB/SD Card File Service

File System

EXT4, FAT, NTFS, HFS+

Access Support

- File explorer (via LAN only)
- Web browsers: Chrome™, Firefox®, Microsoft Edge, Safari
- Mobile device: DS file

Protocol Support

Windows file service (CIFS), Mac file service (AFP), FTP/FTPS, WebDAV

Others

Apple Time Machine

v

Shared Folder Privileges

v

Storage Hibernation

v