



POR-1202, 2-Port Outdoor PoE-Plus Repeater, Cascadable

Product Images



Short Description

- High Power PoE compliant to simplify deployment and installation
- Multiple PoE repeaters can be deployed by daisy chain to extend range
- Forwards Power over Ethernet (PoE) to remote device
- Forwards 802.3af/High-Power PoE to remote device
- Extends PoE connection for another 100 meters
- No additional power supply required
- Simple Plug and Play installation
- Weatherproof IP66-rated housing

Beschreibung

Extend the reach of your PoE-Plus devices. For system integrators looking for a professional solution to help extend their Outdoor PoE (802.3af/at) network, the LevelOne POR-1202 is the perfect accessory to increase your network performance. As a 2-port repeater, it's now easier to add more devices to the network for greater deployment flexibility. Normal cable runs only reach 100 meters, but with POR-1202 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters. Simple yet durable, no software required. As a PoE-Plus Repeater, the POR-1202 receives all power from the Power Sending Equipment (PSE), such as a PoE-Plus switch. This means that the POR-1202 uses no external power supply, making it the most flexible option for system integrators looking for an easy, affordable solution to increase the distance to the attached devices on a network. The POR-1202 has 3 RJ-45 ports for easy deployment, 1 "IN" port that accepts the power and data for the first 100 meters, and 2 "OUT" ports that boosts and extends the power and data an additional 100 meters. The POR-1202 is a long-ranged solution for deploying PoE IP Cameras and any Fast Ethernet PoE PD powered by 802.3at PSE.

* Maximum distance depends on the required Wattage of the PD.

Additional Information

Max. Luftfeuchtigkeit im Betrieb (%)	95
Max. Betriebstemperatur in °C	50
Min. Luftfeuchtigkeit im Betrieb (%)	5
Indikator	Power, PoE In, PoE Out
Befestigung	Pole mount
Pinbelegung und Polarität	1/2 (+), 3/6 (-)
Standards	IEEE 802.3 10Base-T, Ethernet IEEE 802.3u 100Base-TX, Fast Ethernet IEEE 802.3x Ethernet Flow Control IEEE 802.3 af/at PoE
Grundfunktionen	PoE Extension for another 100 meters at 100Mbps
Produktgewicht (kg)	1.08
Produktbreite (mm)	200
Produkttiefe (mm)	270
Produkthöhe (mm)	70
Farbe	Silver
EAN	4015867227312
Modellnummer	POR-1202
Lieferumfang	POR-1202 Mounting Kit Quick Installation Guide

