

**ViewSonic®**



LCD DISPLAY

**VA2762-4K**

## Key Features

- 4K UHD 3840 x 2160 resolution
- SuperClear® IPS panel
- Lifelike color display with 10-bit color depth
- HDMI and Display Port inputs for flexible connectivity
- Eye ProTech for comfortable viewing



## Product Description

The ViewSonic VA2762-4K is a 27" UHD monitor featuring HDMI and Display Port inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through eye-care technology and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.

**Visit Us**

[www.viewsonic.com](http://www.viewsonic.com)

## DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	250 cd/m <sup>2</sup> (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.155 mm (H) x 0.155 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

## COMPATIBILITY

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	3840x2160

## CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)

## POWER

Eco Mode (Conserve):	26W
Eco Mode (optimized):	30W
Consumption (typical):	32W
Consumption (max):	40W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply

## ADDITIONAL HARDWARE

## CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

## OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

## WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

## INPUT SIGNAL

Frequency Horizontal:	HDMI (v2.0): 15 ~ 204KHz, DisplayPort (v1.4): 24 ~ 140KHz
Frequency Vertical:	HDMI (v2.0): 40 ~ 60Hz, DisplayPort (v1.4): 40 ~ 60Hz

## VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

## ERGONOMICS

Tilt (Forward/Back):	-5° / 20°
----------------------	-----------

## WEIGHT (IMPERIAL)

Net (lbs):	10.4
Net Without Stand (lbs):	9.4
Gross (lbs):	13.7

## WEIGHT (METRIC)

Net (kg):	4.7
Net Without Stand (kg):	4.3
Gross (kg):	6.2

## DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	27.6 x 18.1 x 4.6
Physical (in.):	24.2 x 17.9 x 7.4
Physical Without Stand (in.):	24.2 x 14.4 x 2.1

## DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	701 x 461 x 118
Physical (mm):	614 x 456 x 189
Physical Without Stand (mm):	614 x 366 x 53

## GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, BIS
PACKAGE CONTENTS:	VA2762-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male- Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.

Kensington Lock Slot:

1

Warranty:

\*Warranty offered  
may differ from  
market to market

Copyright © ViewSonic Corporation 2000-2024. All rights reserved.