



Delock Cable USB TTL male > 3.5 mm 4 pin stereo jack male 1.8m (3.3 V)

Description

This USB TTL converter by Delock is due to its wide temperature range most suitable for industrial applications. It can be used for e.g. level converter, GPS-modules, interface controller, micro controller etc.



Specification

- Connector: USB 2.0 type A male Serial-TTL male > 3.5 mm 4 pin stereo jack male
- Pin assignment:
 1. GND
 2. TXD
 3. RXD
 4. VCC
- Chipset: FTDI 232RL
- Cable gauge: 28 AWG
- Temperature range: -20°C to +80°C
- No-load current: 70 uA
- Converter: 5 V / 15 mA (VCC, GND)
- Compatible to UHCI / OHCI / EHCI controller
- VTTL 3.3 V (data) / 4 mA or HighLevel 12 mA
- Data rate 300 baud - 3 Megabaud
- Databit: 7 or 8
- Stopbits: 1 or 2
- Parity: none, space, even, odd, mark
- Flow control: software XON/XOFF or hardware RTS / CTS
- FIFO: 128 Byte – RX
256 Byte – TX
- Cable length: ca. 1.80 m

System requirements

- Windows CE 4.2, 5.0, 6.0/Windows Mobile 2003/ XP/XP-64/Vista/Vista-64/7/7-64, Mac OS 10.5 and 10.6, Linux Kernel 2.6
- PC or laptop with a free USB type A port

Package content

- USB TTL cable
- Driver CD
- User manual

Item No. 83779

EAN: 4043619837793

Country of origin: CHINA

Package: Retail Box



Images

