



RAVENOL Formel Super SAE 15W-40

RAVENOL Formel Super 15W-40 is high quality multi-grade engine oil which corresponds to all requirements of modern carburetor and Diesel engines. It can be used in passenger cars as well as trucks. It fulfils the requirements of modern Diesel engines with or without supercharging. The favourable viscosity area ensures a high lubrication capacity all the year under different operation circumstances.

Application Notes

RAVENOL Formel Super 15W-40 can be used according to the manufacturer specification for Diesel as well as Otto engines.

Quality Classifications

RAVENOL Formel Super 15W-40 is tried and tested for aggregates specifying:

Specifications

API SF/CD, ACEA A2/B2

Practice and tested in aggregates with filling

MB-227.1, MIL-L-46152 B, MIL-L-2104 D, CCMC G4 (gültig bis 31.12.96)

Characteristic

RAVENOL Formel Super 15W-40 offers:

- Protection against corrosion
- A very good shear stability
- A very high oxidation stability
- An excellent viscosity temperature behaviour
- Efficient function of hydraulic shock absorbers (hydraulic valve compensation)
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions
- Neutrality against sealing materials
- Very good cold start attributes
- Avoids the formation of conglutinations, pigmenting, coking and accumulation of mud (black sludge) on cylinders, pistons, valves, sparking plugs and in turbo superchargers
- No problems with the use in catalyst vehicles

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	867	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm ² /s	14,2	DIN 51 562
Viscosity at 40°C	mm ² /s	105,4	DIN 51 562
Viscosity index VI		137	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
Flash point (COC)	°C	240	DIN ISO 2592
TBN	mg KOH/g	7,1	ASTM D2896
Sulphated ash	%wt.	0,95	DIN 51 575

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

08.03.2018

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 052039719-40 / 41