

SC-17



LED 

A cost-effective 17" surveillance display with the quality, connectivity and performance essential for any security environment.

With the AG Neovo SC-17, security centres can keep an eye on budgets without losing sight of performance. Digital and analogue video inputs, including looping BNC I/O, minimise installation cost. Auto NTSC/PAL detection, settings key lock and auto settings adjustment reduce maintenance hassle. Quick signal-switching and rapid response time improve surveillance efficiency, while built-in speakers provide an additional level of security. All this and more make the SC-17 the perfect value display choice for any security environment.

- > High 1280 × 1024 SXGA resolution
- > Anti-Burn-in™ technology
- > Video inputs (BNC in x 1, BNC out x 1)
- > Looping video inputs for multiple connections
- > Quick signal-switching time (≤ 0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Key lock function
- > Auto-adjustment for optimal setting
- > Security socket
- > VESA standard wall mount



SC-17

Specifications

SC-17

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	17.0" (433 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	250 cd/m ² (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour	16.7 M
	Response Time	3 ms (GTG)
Horizontal Resolution	TV Lines	550TVL (NTSC), 550TVL (PAL)
Frequency (H/V)		H: 31 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In	3.5 mm Audio Line-in
	Audio Out	3.5 mm Audio Line-in
	Speaker	1W x 2
Power	Power Supply	External
	Power Requirements	DC 12V
	Consumption	< 25W (On)
		< 1.5W (Stand-by)
Plug & Play		< 1W (Off)
Operating Conditions	VESA	DCC 2B
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +15°
Dimensions	Product	372 x 360 x 164mm
	(W x H x D)	(14.6" x 14.2" x 6.5")
	Packaging	424 x 441 x 164mm
Weight	(W x H x D)	(16.7" x 17.4" x 6.5")
Weight	Product Weight	3.6 kg (7.9 lbs)
	Packaged Weight	3.8 kg (8.4 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, CB, FCC, CE, REACH, GOST-R, WEEE, RoHS
Accessories	Supplied	User manual, power cord, power adaptor, 15-Pin D-Sub cable, audio cable, warranty card



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping video inputs allow multiple display connections



Video versatility, including VGA, DVI, S-Video, and BNC In/Out