

**BOSCH**

Invented for life

# Product data sheet

Power tools for trade &amp; industry

Rotary Hammer with SDS plus

## GBH 4-32 DFR



Robustness combined with durability and excellent performance in the SDS plus category

### The most important data

|                                           |           |
|-------------------------------------------|-----------|
| Rated input power                         | 900 W     |
| Impact energy                             | 4.2 J     |
| Drilling dia. concrete, hammer drill bits | 6 – 32 mm |

**Part Number** 0 611 332 161[> More product information](#)

## Technical data

### Technical data

|                                                |                    |
|------------------------------------------------|--------------------|
| Rated input power                              | 900 W              |
| Impact energy                                  | 4.2 J              |
| Impact rate at rated speed                     | 0 – 3,600 bpm      |
| Rated speed                                    | 0 – 800 rpm        |
| Weight                                         | 4.7 kg             |
| Tool holder                                    | SDS plus           |
| Packaging dimensions (width x length x height) | 353 x 473 x 125 mm |
| Voltage, electrical                            | 110 V              |
| Drilling dia. concrete, hammer drill bits      | 6 – 32 mm          |
| Opt. appl. range concrete, hammer drill bits   | 14 – 25 mm         |
| Max. drilling diameter masonry, core cutters   | 90 mm              |
| Max. drilling diameter in metal                | 13 mm              |
| Max. drilling diameter in wood                 | 32 mm              |

### 'Total vibration values (Hammer drilling in concrete)'

|                             |                      |
|-----------------------------|----------------------|
| Vibration emission value ah | 12 m/s <sup>2</sup>  |
| Uncertainty K               | 1.5 m/s <sup>2</sup> |

### 'Total vibration values (Chiselling)'

|                             |                      |
|-----------------------------|----------------------|
| Vibration emission value ah | 9 m/s <sup>2</sup>   |
| Uncertainty K               | 1.5 m/s <sup>2</sup> |

## Noise/vibration information

### Hammer drilling in concrete

|                             |                      |
|-----------------------------|----------------------|
| Vibration emission value ah | 12 m/s <sup>2</sup>  |
| Uncertainty K               | 1.5 m/s <sup>2</sup> |

### Chiselling

|                             |                      |
|-----------------------------|----------------------|
| Vibration emission value ah | 9 m/s <sup>2</sup>   |
| Uncertainty K               | 1.5 m/s <sup>2</sup> |

**BOSCH**

Invented for life

# Product data sheet

Power tools for trade & industry

## Advantages:

- 900 W motor delivers 4.2 J of impact energy for very fast chisel removal rates
- Durable due to robust metal gearbox housing design
- Vibration Control for effortless and continuous work in time-intensive applications

