

ThinkCentre M920 Tower 10SF002F++

Region
EMEA

Machine Type
10SF

TopSeller
TopSeller

Processor
Core i5-8500 (6C, 3.0 / 4.1GHz, 9MB)

vPro
vPro

Graphics
Integrated Intel UHD Graphics 630

Monitor Cable
None

Memory
8GBx1

Storage
256GB SSD M.2 PCIe NVMe Opal

Optional Bay
None

Front Access HDD
None

Optical
DVD±RW

Media Reader
7-in-1

WLAN + Bluetooth
None

Ethernet
Integrated

Optional Rear Ports
None

Chassis Intrusion Switch
Chassis Intrusion Switch

Chassis E-Lock
None

Cable Lock
None

Speaker
2Wx1

Dust Filter
None

Carry Handle
Carry Handle

Stand
None

Keyboard / Mouse
USB / USB

Power Supply
250W 85%

TUV Low Noise
None

Operating System
Windows 10 Pro 64

Warranty
3-year, Onsite

End of Support
Jul 26, 2024

Ann Date (mm/yy)
06/18

Note:
Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "***" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.

© Lenovo, 2018. All rights reserved.



ThinkCentre M920 Tower Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® Celeron®, Intel Pentium®, or 8th Generation Intel Core™ i3 / i5 / i7 Processor						Bluetooth™ Ethernet Ethernet (Opt.)	Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2 Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN® Some: Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4 Some: Bitland BN8E88, gigabit ethernet, 1x RJ-45, PCIe x1 (special bid only)
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics		
	Celeron G4900	2 / 2	3.1G	2 MB	DDR4-2400	UHD 610		
	Celeron G4920	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610		
	Pentium Gold G5400	2 / 4	3.7G	4 MB	DDR4-2400	UHD 610		
	Pentium Gold G5500	2 / 4	3.8G	4 MB	DDR4-2400	UHD 630		
	Pentium Gold G5600	2 / 4	3.9G	4 MB	DDR4-2400	UHD 630		
	Core i3-8100	4 / 4	3.6G	6 MB	DDR4-2400	UHD 630		
	Core i3-8300	4 / 4	3.7G	8 MB	DDR4-2400	UHD 630		
	Core i5-8400	6 / 6	2.8G / 4.0G	9 MB	DDR4-2666	UHD 630		
	Core i5-8500	6 / 6	3.0G / 4.1G	9 MB	DDR4-2666	UHD 630		
	Core i5-8600	6 / 6	3.1G / 4.3G	9 MB	DDR4-2666	UHD 630		
	Core i7-8700	6 / 12	3.2G / 4.6G	12 MB	DDR4-2666	UHD 630		
Memory	64GB max, UDIMM, DDR4-2666*, four 288-pin DIMM sockets, non-ECC, dual-channel capable * System automatically clocks down for the processors with lower memory controller						Manageability	Intel Active Management Technology 12 (Intel AMT 12); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection)
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 Some: DVD-ROM, SATA 1.5Gb/s Drive, slim (9.0mm) Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm) Four onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model)						Security chip	Discrete TPM 2.0, TCG Certified
Optical							Optional 7-in-1 media reader	
Onboard SATA	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle						Security features	● Security slot (in rear for optional Kensington® MicroSaver® cable) ● Padlock loop ● Optional cable lock to physically lock both keyboard and mouse ● Optional chassis intrusion switch ● Optional chassis E-Lock ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement ● Smart USB protection, allows keyboard/mouse only, blocks all storage devices
Media reader							Optional 7-in-1 media reader	
Graphics	Intel UHD Graphics 610/630 in processor, uses main memory, DirectX® 12, one VGA, two DisplayPort™, supports 3 independent displays, works along with discrete graphics to support more displays; Max resolution: 4096x2304 (DP)@60Hz; 2048x1536 (VGA)@50Hz Some: NVIDIA GeForce® GT 730, DirectX 12, 2GB, PCIe 2.0 x8 adapter, two DisplayPort, 35 watts; Max resolution: 3840x2160 (DisplayPort)@60Hz; Some: NVIDIA Geforce GTX 1060 (special bid only), DirectX 12, 6GB, PCIe 3.0 x16 adapter, 1x DVI-D, 1x HDMI, 3x DP, 120 watts, occupies two slots; Max resolution: 2560x1600 (DVI-D)@60Hz; 4096x2160 (HDMI)@60Hz 5120x3200 (DP)@60Hz						Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black
Monitor Cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle						Mouse	Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid) Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)
Chipset							Intel Q370 Chipset	
Front ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x USB 3.1 Type-C Gen1 (15W charging), 1x microphone (3.5mm), 1x headphone / microphone combo jack (3.5mm)						Mechanical	● Tower (18L), black color, metal case ● (WxDxH) 6.5" X 12.65" X 16.15"; 165mm X 321.35mm X 410.25mm ● Approx. 15.45 lb (7 kg), weight may vary by configuration ● Toolless cover, disk, optical, extension card removal ● Optional carry handle, dust filter Bay 1: Slim external ODD bay Bay 2: 5.25", 1.6" high, external, ODD / optional front access HDD Bay 3: 3.5", 1" high, internal, HDD/SSD Bay 4: 3.5", 1" high, internal, HDD/SSD (optional bay, bay comes with disk) Bay 5: 2.5", internal, HDD/SSD (optional bay) Notes: M920 Tower supports up to 3 SATA devices (ODD/HDD/SSD) and 1 eSATA device (front access HDD) Slot 1: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16 Slot 2: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x1 Slot 3: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16 (x4 signal) Slot 4: no slot, only bracket for optional port extension M.2 card slots: Two (one for WLAN, one for SSD/Optane)
Front ports (Opt.)	Optional: 1x media reader						Power supply	Some: 180 watts, autosensing, 85% PSU Some: 250 watts, autosensing, 85% PSU Some: 400 watts, autosensing, 92% PSU (only available via special bid)
Rear ports (Std.)	4x USB 3.1 Gen1, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA, 2x DisplayPort, 1x line-out (3.5mm)						Limited warranty	Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available
Rear ports (Opt.)	Optional: 2x USB 2.0, 2x USB 3.1 Gen1 via PCIe x1, 2x USB 3.1 Type-C Gen2 via PCIe x4 (special bid only), 1x 2nd serial (9-pin), 4x serial (9-pin) via PCIe x1, 1x parallel (25-pin), 2x PS/2 ports (keyboard/mouse), 1x Thunderbolt 3 (combo USB3.1 Type-C Gen 2 / DisplayPort) via PCIe x4, additional RJ-45 and video ports available on optional graphics or ethernet card						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) ● Lenovo Vantage ● Microsoft Office preloaded; purchase a product key to activate ● Cyberlink PowerDVD (only for models with DVD / DVD±RW) ● Cyberlink Power2GO (only for models with DVD±RW) ● LinkedIn
Audio support	High Definition (HD) Audio, Realtek ALC233VB2 / internal speaker (2 watt)						Environment	ENERGY STAR® 6.1, EPEAT™ Gold rating (North America), ErP Lot 3, TCO, TUV low noise verified (coming soon, on some models), RoHS-compliant
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com

Note: The specifications above may not be available in all regions.

Lenovo, July 2018

Lenovo

ThinkCentre M920 Tower

