

FC-WR Flash Commander

- Enabled for wireless Commander Mode
- Quick configuration via independent buttons
- Enables versatile wireless flash photography
- Compact and lightweight design
- Connect unlimited flash units, in up to 3 groups
- Wireless Commander to control multiple flash units remotely from the camera
- Dust, splash & freezeproof



Commander to control flash units

The FC-WR can control multiple flash units remotely from the camera, enabling versatile wireless flash photography. As is the case with the FL-700WR flash, a dust-, splash-, and freezeproof (-10°C) construction allows use in a variety of fields. The commander can connect to three groups and an unlimited number of flash units. The FC-WR has independent buttons for group A, B, and C, making it possible to quickly configure settings for each group as well as adjusting the shooting mode and flash intensity while looking at the monitor. Groups and channels can easily be set and checked with dials on the FC-WR.

Specifications

Illumination

Light intensity	1/1 - 1/128 / 1/3, 1/2 EV steps
Flash compensation	+/- 5 EV / 1/3, 1/2 EV steps

Wireless Flash Control

Modes	TTL Manual FP TTL FP Manual Off
Maximum range	30m / 98.4" *
Frequency band	2.4GHz
Number of channels	15 channels (in the commander mode; with automatic channel setting function)
	3groups (maximum number of unites: unlimited)
	* Measurements obtained from in-house tests at Olympus, using new or fully charged batteries. Actual figures may vary depending on shooting conditions.

Power Supply

Power source	2 AAA batteries
Battery	(Alkaline or Ni-MH)
Battery life	6.4h (using alkaline batteries)

Dimensions

Width	59.5mm
Height	51.0mm
Depth	67.4mm
Weight	73g (excluding batteries)

Environment

Humidity	30 - 90% operation humidity / 10 - 90% storage humidity
Temperature	-10 - 40°C Operating temperature / -20 - 60°C storage temperature
Tough Features	Dust, splash and freezeproof