

# Eaton 5E700UD

Catalog Number: 5E700UD

Eaton 5E Gen2 UPS USB DIN, 700 VA, 360 W, Input: Schuko, Outputs: (2) DIN, Tower

## General specifications

|                     |                      |
|---------------------|----------------------|
| Product Name        | Catalog Number       |
| Eaton 5E Gen2 UPS   | 5E700UD              |
| EAN                 | Product Length/Depth |
| 3553340704192       | 288 mm               |
| Product Height      | Product Width        |
| 148 mm              | 100 mm               |
| Product Weight      | Warranty             |
| 4.31 kg             | 2 year               |
| Compliances         | Certifications       |
| CB                  | IEC/EN 62040-1       |
| LVD Directive       | IEC/EN 62040-2       |
| EMC Directive       | CE                   |
| RoHS Directive      | EAC                  |
| Packaging Directive | Ukr                  |
| WEEE Directive      | IEC/EN 62040-3       |
| Batteries Directive | UKCA                 |
|                     | Cm                   |



## Product specifications

### Secondary frequency - max

60 Hz

### Wattage

360 W

### Form factor

Tower

### Includes network card

No

### Input connection

Protective contact (SCHUKO)

### Input voltage - min

140 V

### Output voltage - max

257 V

### Secondary frequency - min

50 Hz

### Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

### Battery type

Sealed, lead-acid

### Efficiency

95

### Special features

Automatic Voltage Regulation (AVR)

Saves space with a compact tower design

HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)

Includes two Schuko (DIN) Outlets

### Construction type

Free standing model

### Output voltage - min

195 V

### Color

Black

### Extended battery capability

## Resources

### Brochures

[eaton-dpq-5egen2-ups-quickstartguide-en-gb.pdf](#)

### User guides

[eaton-dpq-5egen2-ups-manual-en-gb.pdf](#)

No

Output voltage range

195-257 V

Topology

Line-interactive

Surge protection

Yes

Input nominal voltage

230V default (220/230/240V)

Input frequency range

45-63 Hz

Internal bypass

No

Input voltage - max

300 V

Voltage type

AC

Phase (output)

1

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

Yes

Operating temperature - min

0 °C

VA rating

700 VA

Potential free switch contact

No

Receptacle

(2) Schuko

Phase (input)

1

Package contents

Quick start

Safety instructions

#### Feed type

1

#### Runtime graph

[View runtime graph](#)

#### User interface

LEDs

#### Battery quantity

1

#### Operating temperature - max

40 °C

#### Voltage

230V

#### Hot swap power

No

#### Input cord length

1.5 m

#### Temperature range

0° to 40°C (32° to 104°F)

#### Ethernet interface

No

#### Communication

USB port (HID compliant)

#### Relative humidity

0-90% non-condensing

#### Output apparent power

700 VA

#### Rack mounting kit

No

#### Num of Outputs PC (SCHUKO)

2

#### Output frequency

50/60 Hz

#### Type of interface

USB

#### Primary frequency - min

45 Hz

#### Battery rating

12 V / 7 Ah

Type

UPS

Output nominal voltage

230V

Expansion slots

No

Input voltage range

140-300 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)