

Residual current operated circuit breaker, 4-pole, Type B, short-time delayed, In: 40 A, 30 mA, Un AC: 400 V



Model	
product brand name	SENTRON
product designation	RCCB
design of the product	Short-time delayed
General technical data	
number of poles	4
size of installation devices / acc. to DIN 43880	1
mechanical service life (switching cycles) / typical	10 000
short-circuit current / of series fuse / maximum permissible	100 A
short-circuit current rating	10 kA
switching function / short-term delayed	Yes
overvoltage category	III
Supply voltage	
operational current / at AC / rated value	40 A
<ul style="list-style-type: none"> supply voltage / at AC / rated value 	400 V
<ul style="list-style-type: none"> supply voltage / for testing equipment / minimum 	195 V

supply voltage frequency	
<ul style="list-style-type: none"> • rated value 	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Switching capacity	
switching capacity current	
<ul style="list-style-type: none"> • acc. to EN 60898 / rated value • according to IEC 61008-1 / rated value 	0.8 kA
	0.8 kA
Dissipation	
power loss [W]	
<ul style="list-style-type: none"> • for rated value of the current / at AC / in hot operating state / per pole • maximum 	2.5 W
	7.5 W
Current	
tripping fault current / rated value	30 mA
residual current type	B
let-through current / permissible	6 200 kA
I ² t value / permissible	41 000 A ² ·s
surge current resistance / rated value	3 kA
operational current	
<ul style="list-style-type: none"> • at 40 °C / rated value • at 45 °C / rated value • at 50 °C / rated value • at 55 °C / rated value • at 60 °C / rated value • at 65 °C / rated value • at 70 °C / rated value 	40 A
	40 A
	40 A
	40 A
	40 A
	40 A
	40 A
	40 A
Product details	
product feature / silicon-free	Yes
product extension / installable / supplementary devices	Yes
Connections	
connectable conductor cross-section / solid	
<ul style="list-style-type: none"> • minimum • maximum 	0.75 mm ²
	35 mm ²
connectable conductor cross-section / stranded	
<ul style="list-style-type: none"> • minimum • maximum 	0.75 mm ²
	35 mm ²
tightening torque / with screw-type terminals	

- minimum 2.5 N·m
- maximum 3 N·m

Mechanical Design

height	90 mm
width	72 mm
depth	70 mm
installation depth	70 mm
number of modular width units	4
fastening method	DIN rail (REG)
mounting position	any
net weight	544 g

Environmental conditions

ambient temperature / during operation	
• minimum	-25 °C
• maximum	45 °C
ambient temperature / during storage	
• minimum permissible	-40 °C
• maximum permissible	75 °C
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	28

Certificates

reference code	
• acc. to DIN EN 61346-2	F
• acc. to IEC 81346-2	F

General Product Approval	Declaration of Conformity	other
---------------------------------	----------------------------------	--------------

[Confirmation](#)



[Miscellaneous](#)



[Miscellaneous](#)

other	Railway
--------------	----------------

[Confirmation](#)

[Vibration and Shock](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SV3344-4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SV3344-4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SV3344-4

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



