



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	User manual
--------------------	-------------

### Physical

Cable length	1.52 m
Colour	Black
Depth	6.3 cm
Height	4 cm
Net weight	0.47 kg
Width	30.4 cm

### Input

Input power	2300 W
Network frequency	50/60 Hz
Plug standard	Schuko CEE 7/7P
Switching current capacity	10 A
Input voltage	220 V 230 V 240 V

### Output

Number of power socket outlets	5
Outlet standard	Schuko CEE 7

## Conformance

Product certifications	CE
Marking	CE Mark

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	45 dB
Peak current	15 kA normal mode
Surge energy rate	680 J

## Packing Units

Package 1 Weight	0.551 kg
Package 1 Height	5 cm
Package 1 width	12 cm
Package 1 Length	36.5 cm
SCC14	10731304347030
Number of Units in Package 2	12
Package 2 Weight	7.27 kg
Package 2 Height	270.00 mm
Package 2 width	299.97 mm
Package 2 Length	357.12 mm
Number of Units in Package 3	324

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>