





## IPC 2U-2404L SATA

The **IPC 2U-2404L SATA** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2404L SATA** offers the possibility to mount maximal four 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9.5mm height also a 3.5" HDD simultaneously). The **IPC 2U-2404L SATA** is equipped with three serial 40mm fans. At the rear of the chassis you can mount an ATX PSU with 80mm fan or a Mini-Redundant PS/2 PSU.

Both serial USB 3.0 front connectors round off the whole package.



## **IPC 2U-2404L SATA**

Motherboard	Mini-ITX, µATX		
	max. motherboard size WxD: 244mm x 244mm, 9.6" x 9.6		
Drive Bays	2.5" or 3.5" Hot-Swap (max. 6G): 4 2.5" or 3.5" internal: 1 <sup>1</sup>		
Front Connectors	USB 3.0: 2		
Cooling System	Internal: 3x 40mm (serial, 3Pin with 4Pin connector)		
Controls	Power-Buttor		
	Reset-Buttor		
LED	Powe		
	HDD Activity		
	3x Network Activity		
	1x Aler		
Power Supply	ATX PSU with 80mm fan o		
	Mini-Redundant PS/2		
Material	1.0/1.2mm Stee		
Maximum CPU cooler height	32mm/65mm <sup>*</sup>		
Maximum graphics card length	270mn		
Packing Units	Shipping Unit: 1 Piece Pallet: 21 Piece		
Guarantee and Warranty	Case 24 Months Warranty		
Article Number	8888734		
EAN-Code	4260133128453		
Scope of Delivery	Screw Se		
	Mounting frame for ATX PSL		
_	Mounting too		
Features	Serial 3x 40mm fans		
	4x perforated Low-Profile slot bracke		
	Hot-Swap backplane with S-ATA socket (max. 6G		
	Mesh-Grid-Front with dust filter		
	<sup>1</sup> simultaneously only if 2.5" drive with max. 9.5 mm heigh *depending on the position of the CPU (32mm, if the CPU is under the HDD cage)		

<b>Dimensions and Weight</b>					
		Cage	Case	Package	
	Height	89mm	89mm	155mm	
	Width	433mm	482mm	550mm	
	Depth	480mm	518mm	660mm	
Weight (net): 6.72kg Weight (gross): 8.75kg					

Certification:

CE

