FATHOM E+ 2 PRO



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, powered by Yamaha
STEUERGERÄT	RideControl Dash, full color LCD screen
DISPLAY	RideControl Dash, full color LCD screen
BATTERIE	EnergyPak Smart 625Wh EnergyPak Plus range extender compatible
FRAME	
GRÖSSEN	S, M, L, XL
FARBEN	Gunmetal Black
RAHMEN	ALUXX Aluminum, Overdrive 1½ - 1⅛" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
GABEL	SR Suntour XCR 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1⅛" steerer, lockout
DÄMPFER	-
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal Lock-On
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore LinkGlide
UMWERFER	-
SCHALTWERK	Shimano Deore, 10-speed, LinkGlide, Shadow+
BREMSEN	Tektro HD-M275, hydraulic disc, 180mm [F/R]
BREMSHEBEL	Tektro HD-M275
KASETTE	Shimano Deore LinkGlide CS-M5130-10, 11-43T, 10-speed
KETTE	Shimano, CN-LG500, 9/10/11speed for LinkGlide
KURBELSATZ	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
TRETLAGER	-
LAUFRÄDER	
FELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NABEN	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Stainless steel
REIFEN	Maxxis Minion DHF 29X2.5" 60TPI Foldable, TLR EXO [F] Maxxis Aggressor 29X2.5" 60TPI Foldable TLR EXO [R]
ZUBEHÖR	
BELEUCHTUNG	-

ERFAHREN SIE MEHR....

- Rahmen: ALUXX Aluminum, Overdrive 1½ - 1⅛" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
- Gabel: SR Suntour XCR 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1⅛" steerer, lockout
- Schalthebel: Shimano Deore LinkGlide
- Kurbelsatz: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
- Farben: Gunmetal Black

Preis: € 3.649

GEOMETRIEDATEN

FRAME	S	M	L	XL
Sitzrohrlänge (mm)	405	455	505	535
Sitzrohrwinkel	76,0°	76,0°	76,0°	76,0°
Oberrohrlänge (mm)	575	600	625	650
Steuerrohrlänge (mm)	105	115	125	135
Steuerrohrwinkel	66,0°	66,0°	66,0°	66,0°
Gabel (mm)	51	51	51	51
Spur (mm)	108,5	108,5	108,5	108,5
Radstand (mm)	1204	1231	1258	1285
Kettenstrebenlänge (mm)	475	475	475	475
Tretlager (mm)	45	45	45	45
Stapel (mm)	616	625	635	644
Reichweite (mm)	421	444	467	490
Überstandshöhe (mm)	758	762	794	816
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	60	60	70
Kurbellänge (mm)	160	165	165	170
Radgröße	29"	29"	29"	29"

Preis- und Farbänderungen vorbehalten. Aufgrund der aktuell durch das Corona-Virus verursachten Probleme in den Lieferketten sämtlicher Zulieferer kann das Bike, entgegen der hier kommunizierten Spezifikation, mit abweichenden Komponenten ausgeliefert werden.