DATASHEET

RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, red



Cat.5E | 2.5 Gbit | 100 MHz | 100% CU | made in Europe

Description

The Cat.5e RJ45 **crossover** patch cable **manufactured in Europe** guarantees very good characteristics for 2.5 Gigabit Ethernet applications. The patch cable is composed of the raw cable **UC300 HS26** from Draka and **TM11** connectors from Hirose. Due to the **double shielding**, the patch cable is even **better protected against EMC radiation**.

Cross section 4 x 2 x AWG27/7
Mounted anti-kink grommet
Cable structure **SF/UTP**

General data	
Category	5e
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Connector type	TM11
Cable type	Draka UC300 HS26
Contacts	Gold plated
Pin assignment	other
Allocation	acc. TIA/EIA 568B
Type	Shielded
Anti-kink sleeve	put-on
Colour anti-kink sleeve	red
Locking lever	No

Mechanical characteristics	
Mating cycles	≥750
Bending radius	>25 mm

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, red

Cable construction	
Cable structure	SF/UTP
Cable construction	4x2
AWG-size/strands per core	26/7
Conductor Material	Copper

Cable sheath	
Jacket material	LSZH
Colour outer sheath	red
Outer diameter of the cable	5.7 mm
Flame-retardant	acc. IEC60332-1
Halogen-free	acc. IEC60754-2
Low smoke	acc. IEC61034

Environmental conditions	
Temperature Range (Operation)	-20 – 60 °C
Temperature Range (Installation)	0 – 50 °C

Electrical characteristics	
NVP value	67 %
Impedance	100 ±15 Ω
Conductor resistance DC	130 Ω/km
Loop resistance	< 260 Ω/km
Resistance unbalance	< 3 %
Insulation resistance	> 2000 MΩ
Test voltage	1000 (V DC, 1min) core/core und core/screen

Transmission characteristics	
Bandwidth	100MHz
Transmission	2.5Gbit

Standards, approvals, certifications	
Connector	IEC 60603-7-3

Available variants

Article no.	Title	Length
K2793.0,50	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 0,5m, red	0.5 m
K2793.1	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 1m, red	1.0 m

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, red

K2793.1,5	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 1,5m, red	1.5 m
K2793.2	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 2m, red	2.0 m
K2793.3	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 3m, red	3.0 m
K2793.5	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 5m, red	5.0 m
K2793.10	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 10m, red	10.0 m
K2793.15	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 15m, red	15.0 m
K2793.20	RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, 20m, red	20.0 m

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

RJ45 Crossover Patch cable SF/UTP, Cat.5e, TM11, UC300, red

Technical drawings

Belegung Gigabit Crossover:

1	ws/or	3
2	or	6
3	ws/gn	1
4	bl	7
5	ws/bl	8
6	gn	2
7	ws/br	4
8	br	5

-Schirm beidseitig auf Gehäuse!

Gigabit Crossover Pinning zur Direktverbindung von 2 NICs.
(Bei Switch to Switch oder Switch to NIC nicht zwingend)
Empfohlene Leitung: FTP/SFTP ab CAT5e
Steckverbinder: TM11 oder Stewart CAT5e



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION