



SCHUKO socket outlet 2gang horizontal with hinged cover surface-mounted with labelling field, Locks - differing lockings, enhanced contact protection, Berker W.1

Technical features

Architecture

Technical version	4 cable entries
-------------------	-----------------

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

47893525



IP55

Cover, door

- with hinged cover that falls back, manual clip-in
- Complete housing

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Colour	iron grey
Material	thermoplastic
Surface appearance	mat

Dimensions

Height	76 mm
Width	147 mm
Labelling field (W x H)	50 x 16 mm

Installation, mounting

- for horizontal mounting
- for screw fastening

Connection

Connection terminals	according to IEC 60884-1
----------------------	--------------------------

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

Cable

- 2 additional side cable entries
- with one entry for 2 cables and one entry for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

- with labelling field
- Locks - differing lockings
- enhanced contact protection

Safety

Protection index IP	IP55
- Enhanced contact protection - with 4 identical keys	

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

Instructions

- Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK
- Spare keys and other closures (max. 24) on request.
- As a result of the side cable entries specially suited for installation over workbenches.
- Housing screws, hinged cover springs made of stainless steel.
- Labelling field height arranged for P-touch strips 12 mm.
- The upper and lower entry for cables are laterally offset and therefore particularly suitable for mounting beside door frame or the like
- The locks of an article do have identical lockings.
When ordering several articles those do usually have differing lockings.