

Secvest IP Wireless Alarm Control Panel

Art. no. FUAA10011

Page 1 of 3



- Up to 11 wireless detectors in three zones and 3 additional operating units
- Push notification to iPhone and iPad
- Programming and operation via integrated web server
- Active alarm verification via video motion detection (in conjunction with PIR network camera)
- Alarm images are saved in the alarm panel
- E-mail notification of alarms
- Compatible with IP alarm module
- Internal arming possible
- Voice notification of alarms
- Fast notification through Voice-over-IP calls with voice message in case of alarm

Combining alarm and video technology. For use in flats and smaller properties. The Secvest IP system combines alarm technology with brilliant video technology and thus creates an innovative IP-based system which reliably warns you about break-ins, fire and water – including push notifications for mobile devices. In an emergency, alarms can be verified via a connected PIR network camera which provides a true picture of the situation. The centre can be operated using a web browser or iPhone / iPad application, so that direct access to the Secvest IP wireless alarm centre is not necessary. Internal activation is also possible. The 10 LEDs on the centre are used to indicate its status, plus the status of detectors and operating elements. Alarm messages are completely IP-based. An e-mail is sent in the event of an alarm – including an attached image (when the PIR network camera is connected). Alternatively, the centre can inform you of an alarm by voice message by calling a mobile device, PC or landline phone using VoIP. The optional internal siren is used to indicate local alarms. Additionally, the Secvest IP enables access to the saved alarm images on the connected PIR network cameras. The Secvest IP can be expanded by two IP alarm zones using the optional IP alarm module.

Secvest IP Wireless Alarm Control Panel

Art. no. FUAA10011

Page 2 of 3

Technical Data:

Dimensions	(WxHxD) 193x233x45 mm	Max. operating temperature	55 °C
Active intrusion protection	With mechatronic components (jimmying attempt monitoring only in the active state)	Max. humidity	75 %
Alarming	E-mail, VoIP (landline, cellular communication, VoIP client) and push notification	Max. run time on backup power	5 h
Number of control devices	3	Max. receiving range (outdoors)	100 m
Number of users	2	Max. receiving range (building)	30 m
Number of events	500	Max. sending range (outdoors)	100 m
Number of remote controls	3	Max. sending range (building)	30 m
Number of wireless zones	3	Min. operating temperature	0 °C
Number of virtual IP zones	3	Modulation	FM
Display	Status LEDs	Installation location	With surrounding conditions optimally adjusted for wireless performance
Outputs	1xrelay, 4xtransistor	Net weight	0,76 kg
Battery type	12 V, 1.2 Ah	Power supply unit	External
Operation	Local: via Secvest Key, wireless remote control, wireless additional door lock; remote: online via web interface, iPhone/iPad app	Network protocols	TCP/IP, DHCP, SMTP, DNS, NTP, HTTP
Width	193 mm	Network access	RJ-45 Ethernet 10/100 Base-T
Gross weight	2,56 kg	Backup power supply	Yes
DSL monitoring	Yes	Configuration	Via integrated seb-server
Duplex antenna technology	Yes	Tamper monitoring	Yes
Event log	Yes	Switching outputs	7
Extensible (wireless)	Yes	IP protection class	34
Remote configuration	Yes	Fuse	Reverse polarity protection
Wireless alarm bandwidth	Narrow band	Voltage monitoring	Yes
Radio frequency	868,66 MHz	DC voltage supply	13.8 V
Transmission power	10 mW	Language of instructions	12 V, 1.2 Ah
Housing material	ABS	OSD language	DE, UK, FR, NL, DK
Height	233 mm	Packaging language	DE, UK, FR, NL, DK
Integrated siren	No	Power consumption	1.200 mA
Communication/alarming	email	Partitions/surveillance partitions	1
Length	45 mm	Environmental class	II
Power consumption	13,8 W		

Secvest IP Wireless Alarm Control Panel

Art. no. FUAA10011

Page 3 of 3

Technical Data:

Supported browsers	Safari 5, Mozilla Firefox 5, Google Chrome, Internet Explorer 9
--------------------	---

Video verification	Optional with PIR network camera
Access protection	User name, password

International Switching-Mode Power Supply 13,8 V/1,7 A

Dimensions	(W x H x D) about 44 x 69 x 83 mm
Width	44 mm
Housing material	ABS
Height	69 mm
Cable length	1,5 m

Length	83 mm
AC voltage supply	100 - 240 V
DC voltage supply	13,8 V
Power consumption	1.750 mA