


41081404





SCHUKO socket outlet with overvoltage protection with labelling field, Screw terminals, Berker B.7, aluminium, matt, lacquered

Technical features

Architecture

Design	according to DIN 49440

Controls and indicators

- with acoustic fault signal

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Voltage

Overvoltage protection	according to EN 61643 and VDE 0675-6-11

Cover, door

- Central cover plate

Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

Dimensions

Insertion depth	32 mm

Installation, mounting

- with spreader claws

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1

- with screw terminals

Equipment

- with indicator LED for On/Error

Use

- with labelling field
- Screw terminals

Safety

Protection index IP	IP20
IK protection code against mecanical impacts	05
- without enhanced contact protection	

Identification

Main design line	Berker B.7
Secondary design line(s)	Berker B.1, Berker B.7

Instructions

- Labelling field height arranged for P-touch strips 6 mm.