

Product datasheet

Specifications



Easy PDU, Metered, Zero U, 22 kW, 230V, (18) C13 & (6) C19;IEC309

EPDU1232M

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	400 V 3 phases
Main Output Voltage	230 V
Plug standard	IEC 60309 32 A 3P + N + PE
Number of rack unit	0U
Cable length	1.98 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Physical

Colour	Black
Height	150.6 cm
Width	6.2 cm
Depth	4.44 cm
Net weight	4.64 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Input current limits	32 A
Load capacity	22000 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	18 IEC 60320 C13 6 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product certifications	CE EAC RCM TÜV
------------------------	-------------------------

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	5.48 kg
Package 1 Height	1.66 m
Package 1 width	160 mm
Package 1 Length	110 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------