PRODUCT DATASHEET
ST CLAS B 60 7.5 W/2700K E14

LED STAR CLASSIC B | LED lamps, classic mini-candle shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Chandeliers
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Low energy consumption
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- LED alternative to conventional lamps
- Mercury-free lamps



© 2020, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Rated wattage	7.50 W
Nominal wattage	7.50 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	140
Max. lamp no. on circuit break. 16 A (B)	228
Operating frequency	50...60 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W


Photometrical data

Rated luminous flux	806 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	806 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80

Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & weight



Overall length	115.0 mm

© 2020, LEDVANCE GmbH. All rights reserved.

Diameter	39.0 mm
Outer bulb	B39
Length	115.0 mm

Temperatures & operating conditions

Ambient temperature range	-20…+40 °C
Maximum temperature at tc test point	100 °C

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E14
Mercury-free	Yes
Show WEEE picto	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Mercury content	0.0 mg

Capabilities

Dimmable	No

Certificates & standards

Energy efficiency class	A+
Energy consumption	8 kWh/1000h

Country-specific categorizations

Order reference	LEDSCLB60 7,5W/

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075428546	Folding carton box 1	41 mm x 49 mm x 155 mm	45.00 g	0.31 dm^3
4058075428553	Shipping carton box 10	226 mm x 111 mm x 131 mm	536.00 g	3.29 dm^3

© 2020, LEDVANCE GmbH. All rights reserved.

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For further products and actual information concerning LED lamps see

- www.ledvance.com/ledlamps

For Guarantee see

- www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2020, LEDVANCE GmbH. All rights reserved.