

Eaton NG8POE-M2

8-Port 2.5Gigabit Unmanaged Network Switch w PoE+, 100W



Allgemeine Spezifikation

PRODUCT NAME	Eaton Tripp Lite series unmanaged ethernet switch
CATALOG NUMBER	NG8POE-M2
PRODUCT LENGTH/DEPTH	4.13 in
PRODUCT HEIGHT	1.06 in
PRODUCT WIDTH	9.45 in
PRODUCT WEIGHT	1.52 lb
COMPLIANCES	UKCA IEEE Certified RoHS FCC Class B TAA Compliant CE Marked
CERTIFICATIONS	EN 55032 NOM EN 55035
UPC	037332287205

Produktspezifikationen

TYPE	• Fanless • Unmanaged Network Switch
-------------	--

FREQUENCY RATING	50/60 Hz
-------------------------	----------

INPUT PLUG TYPE	NEMA 5-15P Schuko
------------------------	----------------------

PACKAGE CONTENTS	NG8POE-M2 8-Port 2.5 Gb Unmanaged Switch External power supply NEMA 5-15P to C13 power cord, 5 ft. (1.5 m) Schuko to C13 power cord, 5 ft. (1.5 m) Rubber mounting feet Owner's manual
-------------------------	---

PRODUCT HIGHLIGHTS	Capable of 2.5 Gb Ethernet network speeds ideal for high-bandwidth applications Supports PoE to save you expense and effort of powering PoE devices individually 8 twisted-pair auto-negotiable RJ45 ports support auto MDI/MDIX functionality Unused ports shift into low-power state without interrupting network connection IEEE friendly: supports 802.3az Energy Efficient Ethernet standards
---------------------------	--

FORM FACTOR	Desktop Wall-mount
--------------------	-----------------------

VOLTAGE COMPATIBILITY (VAC)	100 - 240 VAC
------------------------------------	---------------

NETWORK COMPATIBILITY	100 Mbps (Fast Ethernet) 1 Gbps (Gigabit) 2.5 Gbps
------------------------------	--

NUMBER OF PORTS (OTHER)	9
--------------------------------	---

POWER CONSUMPTION - MAX	120 W
--------------------------------	-------

ELECTRICAL CONSUMPTION (MAX POE LOAD)	100W
--	------

ELECTRICAL CONSUMPTION (MAX)	120W
-------------------------------------	------

POE CAPABILITY	30W (802.3at)
-----------------------	---------------

Downloads

POE POWER BUDGET (WATTS)	100
POE SUPPORTED PORTS	8
PORTS DETAIL	(x8) 2.5Gigabit RJ45 Ethernet Ports (x1) 10Gb SFP+ Port
COLOR	Black
CORD LENGTH	5 ft
FORM FACTORS SUPPORTED	Desktop, Wall mount
MATERIAL	Metal
OPERATING TEMPERATURE	0° to 104°F (0° to 40°C)
OPERATING TEMPERATURE RANGE	0° to 104°F (0° to 40°C)
RELATIVE HUMIDITY	5% - 90%, RH (Non-condensing)
STORAGE TEMPERATURE RANGE	-40° to 158°F (-40° to 70°C)
NETWORK COMPATIBILITY DETAILS	Auto-negotiable
LED INDICATOR	(x1 Green)PWR, (x8 Green) PoE, (x1 Green) PoE/MAX , (x8 Amber) 1-8 100M/1000M Link, (x8 Green) 2.5G Link, (x1 Blue) 10Gb SFP+ Uplink
SFP UPLINK PORTS	1
SFP UPLINK PORTS DETAIL	(x1) 10Gb SFP+ port
STORAGE HUMIDITY RANGE	5% - 90%, RH (Non-condensing)
SWITCHING CAPACITY	60Gbps
SWITCHING CAPACITY DETAILS	5Gbps per port with full duplex
JUMBO FRAMES	12000
MAC ADDRESSES	4000
FANS (TYPE/QUANTITY)	Fanless
NETWORK SWITCH PORTS	10/100/1000 (RJ45) Dedicated SFP
POE TYPE	Type 2 PoE+ (30W, IEEE 802.3at)

PROJEKTNAME:

PROJEKTNUMMER:

ERSTELLT VON:

DATUM:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

© 2025 Eaton. Alle Rechte vorbehalten.

Folgen Sie uns in den sozialen
Netzwerken und erhalten Sie aktuelle
Produkt- und Supportinformationen.

