




WaveLine Wall sensor 2-gang Wireless aluminium silver - Platform 63

Product is not offered in Germany .

Archive



General Information

Extended Product Type: 6732-83

Product ID: 2CKA006730A0052

EAN: 4011395149942

2gang wall-mounted transmitter independent of mains power supply. With labelling field and labelling strip. For switching and dimming. For controlling blinds and light scenes. 2 radio channels can be operated or up to 4 light scenes can be called up. For flush-mounted WaveLINE actuators 6701-101, 6702, 6703, 6704 and 6705-101. Send frequency: 868 MHz. Free-field range: approx. 100 m. Power supply: lithium button cell battery Type CR2032. Battery service life: typically 5 years, therefore practically maintenance-free. Automatic monitoring of battery life. Including fixing plate for mounting on smooth walls or on switch boxes.

[Go to Labeling Tool](#)

Installation

Instructions and Manuals: [Installation and Operating Instructions \(.PDF\) \[DE\] 673X-XXX \(2CKA000073B7534\)](#)

Mounting Type: Surface Mounted
Flush Mounted

Mounting Position: Wall

Modular Components Included: Cover Plate

Environmental

Ambient Air Temperature: Operation -5 ... +45 °C

Degree of Protection: IP20

Technical

Product Range: WaveLINE

Transmission Standard: Wireless

Number of Batteries: 1

Battery Size: CR2032

Battery Chemical Composition: Lithium Metal

Battery Integration Type: Replaceable Non-Rechargeable

Battery Life: 5 year

Battery Weight: 3 g

Battery Lithium Amount: 0.075 g

Battery Report UN 38.3: [Battery Report according UN 38.3 \(.PDF\) \[EN\] Renata CR2032 \(9AKK108471A9996\)](#)

Electrical

Rated Voltage (U_r): 3 V

Frequency (f): 868 MHz Hz

Design

Design Range: Platform 63

	future linear
	Busch-axcent
Design Range Variant:	Busch-axcent Busch-axcent pur
Surface Finishing:	Lacquered Matt
Material:	Thermoplastic
Label Space Provided:	With Label Space
RAL Number:	Similar to RAL 9006
Color:	aluminium silver
Number of Gangs:	2-gang

Dimensions

Product Net Width:	63 mm
Product Net Height:	63 mm
Product Net Depth / Length:	15.6 mm
Product Net Weight:	33.5 g

Material Compliance

RoHS Declaration:	ROHS Product Declaration (.PDF) [EN] 6732-83 (2CKA200000E6237)
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration:	REACH Declaration of Conformity (.PDF) [EN] (2CKA309999E9999)
REACH Information:	False - does not contain substances > 0.1 mass percentage
REACH Date:	20250901
Conflict Minerals Reporting Template (CMRT):	Conflict Minerals Reporting Template (9AKK108468A3363)

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B: Business To Consumer

Battery Type: Button Cell

Certificates and Declarations

Declaration of Conformity - CE: [EU-Declaration of conformity \(.PDF\) \[EN\] 6732-83 \(2CKA100000E0673\)](#)

EU Data Act Applicability and Compliance: Not Applicable

External Classifications and Standards

ETIM 9: EC000257 - Transmitter/Remote control for domestic switching devices

ETIM 10: EC000257 - Transmitter/remote control for domestic switching devices

eClass: V11.0 : 27144039

Dangerous Goods UN Number: 3091
