



Delock Adapter USB 2.0 to 1 x serial RS-422/485

Description

This USB 2.0 to serial adapter enables you to connect a serial device to a free USB port.



Specification

- Connector:
 - 1 x USB 2.0 type B female >
 - 1 x serial RS-422/485 DB9 male
- Chipset: FT232HL, SP3078EE
- 1 x DIP switch: RS-422/485 operation setting
- Internal pin header: Jumper switch terminator on / off
- Serial male connector with screw nuts
- Data transfer rate up to 1 Mb/s
- LED for indication of TxD / RxD activity
- Automatical recognition and switching between RS-422 and RS-485
- ±15KV ESD protection on all signal pins
- Wall mounting integrated in the housing
- Power consumption:
 - operation: ≤ 61 mA / 305 mW
 - standby: ca. 16 mA / 80 mW
- Additional I/O and IRQ are not required
- Dimensions (LxWxH): ca. 80 x 72 x 23 mm

System requirements

- Windows Vista/Vista-64/7/7-64/8/8-64, Linux Kernel 2.6
- PC or Notebook with a free USB port

Package content

- USB 2.0 to 1 x serial RS-422/485 adapter
- USB 2.0 cable
- 2 jumper
- Driver CD
- User manual

Item No. 87585

EAN: 4043619875856

Country of origin: China

Package: Box



Images

