



SCHUKO socket outlet 3gang horizontal with hinged cover surface-mounted Berker S.1/B.3/B.7, grey/light grey matt

Technical features

Architecture

Design	according to DIN 49440
--------	------------------------

Main electrical features

Nominal voltage	250 V
Rated current	16 A
Rated voltage	250 V AC

Cover, door

- with hinged cover that falls back, manual clip-in
- Complete housing

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Colour	iron grey
Material	thermoplastic
Surface appearance	matt

Installation, mounting

- for horizontal mounting
- for screw fastening

Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
- with two clip-in places for Wago 2-wire connection terminals in the housing floor - with Wago clip-in 2-wire connection terminal for wiring - with plug-in terminals	

Cable

- inserts wired-through
- with one entry for 2 cables and 2 entries for cable and tube

Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Safety

Protection index IP	IP55
IK protection code against mechanical impacts	05
- without enhanced contact protection	

47733515



IP55

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Application, usage	Surface-mounted wet-room installation
Main design line	Berker S.1/B.3/B.7

Instructions

- Hinged cover springs made of stainless steel, pins of quick-release lock made of ZAMAK