


RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, black



Description

The Cat.6A RJ45 patch cable **manufactured in Europe** guarantees very good characteristics for **10 Gigabit** Ethernet applications. The patch cable is composed of the Cat.7 raw cable **CU 7702 flex** from Daetwyler and **TM21** connectors from Hirose.

Cross section 4 x 2 x AWG26/7

Mounted anti-kink grommet

Clear differentiation of the cores in the assembled connector thanks to different core colours

General data

Category	6A (TIA)
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Connector type	TM21 red
Cable type	Dätwyler CU 7702 flex
Contacts	Gold plated
Pin assignment	1:1
Allocation	acc. TIA/EIA 568B
Type	Shielded
Anti-kink sleeve	put-on
Colour anti-kink sleeve	black
Locking lever	Yes

Mechanical characteristics

Mating cycles	≥750
Bending radius	>20 mm
Conductive shield	360° shield contact

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.



RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, black

Cable construction

Raw cable	Cat.7
Cable structure	S/FTP
Cable construction	4x2
AWG-size/strands per core	26/7
Conductor Material	Copper

Cable sheath

Jacket material	LSZH
Colour outer sheath	black
Outer diameter of the cable	5.8 mm
Flame-retardant	acc. IEC60332-1
Halogen-free	acc. IEC60754-2
Low smoke	acc. IEC61034

Environmental conditions

Temperature Range (Operation)	-20 – 60 °C
Temperature Range (Installation)	0 – 50 °C

Electrical characteristics

NVP value	78 %
Impedance	100 ±5 Ω
Conductor resistance DC	135 Ω/km
Loop resistance	270 Ω/km

Transmission characteristics

Bandwidth	500MHz
-----------	--------

Standards, approvals, certifications

Connector	IEC 60603-7-51
-----------	----------------

Available variants

Article no.	Title	Length
K8708SW.0,5	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 0,5m, black	0.5 m
K8708SW.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 1m, black	1.0 m
K8708SW.1,5	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 1,5m, black	1.5 m
K8708SW.2	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 2m, black	2.0 m
K8708SW.3	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 3m, black	3.0 m

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.

RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, black

K8708SW.5	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 5m, black	5.0 m
K8708SW.7,5	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 7,5m, black	7.5 m
K8708SW.10	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 10m, black	10.0 m
K8708SW.15	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 15m, black	15.0 m
K8708SW.20	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 20m, black	20.0 m
K8708SW.25	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 25m, black	25.0 m
K8708SW.30	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, 30m, black	30.0 m

Technical drawings



- 1 Innenleiter: AWG26, Cu-Litze, blank
- 2 Ader: Ø 0.99 mm
- 3 Abschirmung Paar: Alu PETP-Folie
- 4 Abschirmung: Cu-Geflecht, verzinkt
- 5 Mantel: LSZH, grau, RAL 7035

Belegung: 1 -sw- 1

2 -gn- 2

3 -rt- 3

4 -bl- 4

5 -ws- 5

6 -or- 6

7 -ge- 7

8 -br- 8

Schirm beidseitig auf Gehäuse!

Farbe / Code

weiß /blau, rot/orange, schwarz/grün, gelb/braun, nach IEC 60189 und IEC 60708

similar product

K8708OR.1,5	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, orange
K8708RT.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, red
K8708GR.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, grey
K8708GN.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, green
K8708GE.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, yellow
K8708BL.1	RJ45 Patch cable S/FTP, Cat.6A, TM21, Dätwyler 7702, blue

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.