



KEY FEATURES

- Intel® 11th Gen (Tiger Lake-UP3) Core™ Processors
- 2 x 260-pin SO-DIMM up to 64GB DDR4 3200 MHz
- 5 x USB 3.2 Gen2, 1 x M.2 Key M, 1 x M.2 Key E (WiFi-6 AX200), 1 x SATA3
- 1 x Intel 1 Gigabit LAN, 1 x Intel 2.5 Gigabit LAN
- Supports Quad display, 1 x HDMI 2.0a, 3 x DP 1.4 (2 from Type C)
- TPM onboard
- 19V/90W Power Adapter
- 110.0 x 117.5 x 47.85mm, Fanned Barebone

SPECIFICATIONS

Processor System

CPU	NUC BOX-1165G7 (I7-1165G7, QC, Max Speed up to 4.7GHz) NUC BOX-1135G7 (I5-1135G7, QC, Max Speed up to 4.2GHz) NUC BOX-1115G4 (I3-1115G4, DC, Max Speed up to 4.1GHz)
Chipset	MCP
BIOS	AMI SPI 256 Mbit

Memory

Technology	Dual Channel DDR4 3200 MHz
Capacity	64GB (32 GB per DIMM)
Socket	2 x 260-pin SO-DIMM

Graphics

Controller	Intel® Iris® Xe Graphics for i7/i5 CPU Intel® UHD Graphics for i3/Celeron CPU
HDMI	HDMI 2.0a Max resolution up to 4096x2160@60Hz
DisplayPort	DisplayPort 1.4, DP++ Max resolution up to 4096x2160@60Hz
MultiDisplay	Quad-Display (Included 2 outputs from Type-C)

Expansion Slot

M.2/ WLAN	1 x Intel® Wi-Fi 6 AX200 module (M.2 Key E, 2230 PCIe x1, USB 2.0 for Wireless)
-----------	--

Audio

Interface	Realtek ALC233, High Definition Audio.
-----------	--

Ethernet

Controller/ Speed	LAN1: Intel® I219V with 10/100/1000 Mbps LAN2: Intel® I225LM with 10/100/1000/2500 Mbps
Connector	2 x RJ-45

Storage

M.2	1 x M.2 (Key M, 2242/2260/2280) with SATA3 and PCIe Gen4 x4 for SSD *M.2 Key M 2280(Supported by bracket)
SATA	1 x SATA3.0 (6.0 Gb/s)

Front I/O

USB	1 x USB 3.2 Gen2 (Type A) 2 x USB 3.2 Gen2 (Type-C, Supports DP1.4 display output) * USB4™ Compliance Test is pending for certification
Audio	1 (headphone & microphone jack)

Rear I/O

HDMI	1 x HDMI 2.0a
DisplayPort	1 x DP1.4
Ethernet	1 x 1 Gigabit LAN, 1 x 2.5 Gigabit LAN
USB	2 x USB 3.2 Gen2 (Type-A)
DC Jack	1

Watchdog Timer

Output	From Super I/O to drag RESETCON#
Interval	256 Segments, 0, 1, 2, ...255sec

Power Requirements

Input PWR	1 x 19V/90W Power Adapter
Power On	AT/ATX Supported - AT : Directly PWR on as power input ready - ATX : Press button to PWR on after power input ready

Environment

Operating Temp	0°C ~ 40°C
Storage Temp	-40° C – 85° C
Operating Humidity	5% ~ 90%
Storage Humidity	5% ~ 90%

Mechanical

Construction	Plastic
Mounting	VESA mounting
Dimensions (W x D x H)	110.0 x 117.5 x 47.85mm
Weight	Net Weight:1.0Kg

Others

OS Support	Windows 10
Certifications	CE, FCC Class A
Packing List	1 x 19V/90W Power Adapter 1 x Screw Package 1 x VESA mounting bracket