



ALL - AROUND DATA PROTECTION.

Thoughtfully Designed Protection At Every Corner

Protective silica gel bubbles around the perimeter transform into exterior slots for the cable to be stored and dually function as a handle. An internal rubber suspension system keeps the hard drive securely in place and away from direct contact with drops or bumps. A distinguished yet subtle hexagonal pattern promotes resistance from scratches that naturally occur from regular use.



USB 3.2 Gen 1: Edit, Transfer, Move On, Quickly

With super-speed USB 3.2 Gen 1 interface, the Armor A30 delivers swift read and write speeds. Up to 5Gbps cuts the time needed to edit or transfer large files, including HD graphics and videos, to get the job done faster so you can move on to the next project. And with up to 2TB storage capacity, you'll have more than enough space to work with those large files.



Portable HD Armor A30

1 TB | 2TB



Features

- Super-speed data transfer with USB 3.2 Gen 1 interface (up to 5Gbps)
- 3-meter freefall test and 3m military-grade shockproof enclosure (MIL-STD 810G Method 516.6 Procedure IV)*
- Internal silica gel suspension system and external silica gel bubbles keeps your hard drive safe from drops and bumps
- Convenient wrap-around cable design prevents cable misplacement and allows for easy portability as a handle function
- Hexagonal pattern on the surface promotes scratch resistance
- LED light indicates data transfer activity and power status
- Easy "plug-in and use" eliminates the need for an external adapter
- Customization available (by request)
- Free SP Widget software available for download, which provides 7 major back-up and security functions

* Product meets the test standards under normal use. Do not deliberately drop or damage the product.

Specifications

- Capacity: 1TB, 2TB
- Dimensions: 134mm x 87.5mm x 18.6mm
- Weight: 181g - 205g (by capacity)
- Material: Rubber + Plastic
- Color: Black/Orange, White/Grey, Black/Black
- Interface: USB 3.2 Gen 1 (USB 3.0, USB 2.0 backwards-compatible)
- OS Compatibility: Windows 10/8.1/8/7/Vista/XP 64-Bit, Mac OS 10.5.x, Linux 2.6.x
- Operating Temperature: 5°C - 55°C
- Storage Temperature: -40°C - 70°C
- Operation Voltage: DC 5V
- Certification: CE, FCC, BSMI, Green dot, WEEE, RoHS, KCC, RCM
- Patent: TW Patent: D160484
- Warranty: 3 years