CITIZEN

Print - Stick - Done

Market-leading, Eco-friendly POS printing solution



The upgraded CT-S601IIR

A new and special version of the popular CT-S601II printer, the new CT-S601IIR arrives as a Re-Stick Liner-Free Model that prints top exit, self-adhesive labels and has been designed to serve across multiple applications.

Eco-friendly POS printing solutions

Producing cost-effective, continuous roll label output, the CT-S601IIR also highlights mark-leading eco-friendly capabilities. Offering users significant waste reduction, the new printer produces entirely Liner-Free labels and is compatible with MAXStick® media. Also, due to its ability to adjust the print length to suit the required content, CT-S601IIR reduces waste further still.

Internal power supply

All 80mm POS printers from Citizen offer an internal power supply.

TOMORROW'S PRINTING TODAY

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

Applications



Available in either sleek black or classic ivory

CITIZEN SYSTEMS EUROPE GMBH

CITIZEN



Supported by an adaptable range of optional interfaces including USB, LAN, WiFi, Bluetooth and others.

Specifications

CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Low space requirement - integrated power supply enables clean work station
- Mobile-POS ready



Producing super-fast, liner-free labels up to 83 mm wide, at a speed of 175 mm per second and at 203 dpi

CITIZEN SYSTEMS EUROPE GMBH

CITIZEN

CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

Model	CT-S601IIR
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	175mm/sec
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65µm to 90µm
Media Sensor	Paper end
Main Interface	None: interface card slot for optional card
Interface	Parallel (IEEE 1284 compliant), Serial (RS-232C compliant), USB, Premium Wireless LAN, Ethernet (SEH), Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Ethernet, Ethernet + USB host, USB 2.0, Powered USB
Power supply	100 – 240V, 50-60 Hz, external power supply (supplied) or 24V DC
Reliability	100 million pulses, 75km
Control panel	Feed button, 3 LEDs
Emulations (Languages)	ESC/POS™
Drivers and software	Free-of-charge from website, including support for various platforms
Size (W x D x H) and Weight	145x192x148 mm, 2 Kg, DC version 145x192x120, 1.6 Kg
Cutter	Guillotine type, partial
EMC and safety standards	CE, UL, TUV, C-UL, FCC class A, VCCI

CITIZEN

CT-S601IIR

POS, Receipt printer (thermal 3 inch / 80mm)

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

CITIZEN SYSTEMS EUROPE GMBH