

POI-3015, 2.5 Gigabit PoE Injector, 802.3 af/at, 30W

Product Images



Short Description

- Auto-detection and protection of non-standard PoE devices
- IEEE 802.3af/at/bt PoE compliant to simplify deployment and installation
- 10/100/1000/2500 Mbps wire speed transmission and reception
- Support Wall mount installation .
- Total PoE power budget: 30W

Description

The POI-3015 is a single-port, high-power 30W PoE PSE solution designed for remote PoE-powered devices. Delivering up to 30W over all 8 pins, it supports demanding applications such as wireless access points, pan-tilt-zoom (PTZ) IP cameras, digital signage displays, LED lighting, and video phones.

Compliant with IEEE 802.3bt standards, the POI-3015 provides 30W power via both end-span and mid-span pairs, ensuring stable and efficient power delivery. It also supports data transmission speeds of up to 2.5 Gbps, making it compatible with high-speed network devices

Additional Information

Code des Harmonisierten Systems (HS)	851762
Zolltariflicher Warencode (TARIC)	851762
Injector Port Type.	Single Port
Grade.	Commercial
Dimensions (W x D x H).	64.4x145.7x41.8
Produktgewicht (kg)	0.2
Datenrate	10/100/1000/2500 Mbps
Data Rate.	2.5Gbps
Befestigung	Wall mount
Pinbelegung und Polarität	1/2 (+), 3/6 (-) & 4/5 (+), 7/8 (-)
Port Configuration	Data/ PoE
Energieverbrauch	2W
Eingangsspannung	100-240 VAC
Power supply included.	Ja
Standards.	IEEE 802.3 10-BASE-T, Ethernet, IEEE 802.3ab 1000BASE-T, Gigabit Ethernet, IEEE 802.3af Power over Ethernet (PoE), IEEE 802.3at Power over Ethernet Plus (PoE+), IEEE 802.3bz 2.5 Gigabit Ethernet
Zulassungen und Konformität	CE/FCC
Operating humidity.	0% RH ~ 90% RH
Operating temperature.	0°C ~ 40°C
Storage humidity.	5% RH ~ 90% RH
Storage temperature.	10°C ~ 85°C
Lieferumfang	Power Cord Quick Installation Guide Declaration of Conformity
Farbe	Schwarz
EAN	4015867241592

