

HA1200R-PM

CONN	PIN	COLOR	OUTPUT	AWG	LENGTH(mm)
PA	1	BLACK	+3.3V	16	600 ± 10
	2	BLACK	+3.3VS		
	3	BLACK	+3.3V		
	4	BLACK	GND		
	5	BLACK	+5V		
	6	BLACK	+5VS		
	7	BLACK	GND		
	8	BLACK	PWR-OK		
	9	BLACK	+5VSB		
	10	BLACK	+12V		
			+12VS		
	11	BLACK	+12V		
			+12VS		
	12	BLACK	+3.3V		
	13	BLACK	+3.3V		
	14	BLACK	-12V		
	15	BLACK	GND		
	16	BLACK	PS-ON		
	17	BLACK	GND		
	18	BLACK	GND		
	19	BLACK	GND		
	20	NC	-5V		
	21	BLACK	+5V		
	22	BLACK	+5V		
23	BLACK	+5V			
24	BLACK	GND			
PB	1	BLACK	GND	16	750 ± 10
	2	BLACK	GND		
	3	BLACK	GND		
	4	BLACK	GND		
	5	BLACK	+12V		
	6	BLACK	+12V		
	7	BLACK	+12V		
	8	BLACK	+12V		
PD1	1	BLACK	+12V	16	600 ± 10
	2	BLACK	+12V		
	3	BLACK	+12V		
	4	BLACK	GND		
	5	BLACK	GND		
	6	BLACK	GND		
	7	BLACK	GND		
	8	BLACK	GND		
PD2	1	BLACK	+12V	18	150 ± 5
	2	BLACK	+12V		40 ± 5
	3	BLACK	+12V		150 ± 5
	4	BLACK	GND		
	5	BLACK	GND		
	6	BLACK	GND		
	7	BLACK	GND		40 ± 5
	8	BLACK	GND		
P2	1	BLACK	+12V	16	600 ± 10
	2	BLACK	+12V		
	3	BLACK	+12V		
	4	BLACK	+12V		
	5	BLACK	+12V		
	6	BLACK	+12V		
	7	BLACK	GND		
	8	BLACK	GND		
	9	BLACK	GND		
	10	BLACK	GND		
	11	BLACK	GND		
	12	BLACK	GND		
S1	BLACK	PWR-ENABLE	28	600 ± 10	
S2	BLACK	ENL. -PULSE			
S3	BLACK	Sense 0			
S4	BLACK	Sense 1			

CONN	IN	COLOR	OUTPUT	AWG	LENGTH(mm)
PE1	1	BLACK	+3.3V	18	600 ± 10
	2	BLACK	GND		
	3	BLACK	+5V		
	4	BLACK	GND		
	5	BLACK	+12V		
PE2 FE3 FE4	1	BLACK	+3.3V	18	150 ± 5
	2	BLACK	GND		
	3	BLACK	+5V		
	4	BLACK	GND		
	5	BLACK	+12V		
PF1	1	BLACK	+12V	18	600 ± 10
	2	BLACK	GND		
	3	BLACK	GND		
	4	BLACK	+5V		
PF2 PF3	1	BLACK	+12V	18	150 ± 5
	2	BLACK	GND		
	3	BLACK	GND		
	4	BLACK	+5V		
PB	1	BLACK	+5V	22	101 ± 5
	2	BLACK	GND		
	3	BLACK	GND		
	4	BLACK	+12V		

