P C375

MAIN SPECIFICATIONS

GENERAL

Warm-up time	32 seconds
First output speed: B/W	4.1 seconds
First output speed: full colour	5.3 seconds
Continuous output speed	A4/LEF (1-sided): BW, full colour (32 cpm, 32 cpm) A4/LEF (2-sided): BW, full colour (16 cpm, 16 cpm)
Memory: standard	2 GB
Weight	25 kg
Dimensions: W x D x H	410 x 429 x 360 mm
Power source	220 - 240 V, 50/60 Hz
Storage: standard	32 GB

PRINTER

CPU	QB6640-23UF 1.2GHz
Printer language: standard	PCL5c PCL6 PostScript 3 (emulation) PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript®3™ PDF Direct from Adobe®
Print resolution	1,200 x 1,200 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB Host I/F Type A USB Device I/F Type B
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac) Additional NIC (2nd port)
Mobile printing capability	Apple AirPrint Mopria® Ricoh Smart Device Connector
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 10 Windows® 11 Windows® Server 2016 Windows® Server 2019 Windows® Server 2022
Mac OS environments	Macintosh OS X v10.15 or later

PAPER HANDLING

Recommended paper size	Standard paper tray(s): : A4, A5, A6, B5, B6 Optional paper tray(s): : A4, A5, B5, B6 Bypass tray: : A4, A5, A6, B5, B6, Envelopes, Custom Size paper (bypass tray): (Width: 76.2 mm - 216 mm, Length: 127 mm - 356 mm)
Paper input: standard	250 sheets
Paper input: bypass	50 sheets
Paper input: maximum	1,300 sheets
Paper output: standard	200 sheets
Paper weight	Trays: : 60 - 200 g/m² Bypass: : 60 - 200 g/m² Duplex: : 60 - 163 g/m²
Paper types	Plain paper Recycle paper Special paper Color paper Letterhead Envelope Label paper

ECOLOGY

Power consumption: max.	Less than 1,420 W
Power consumption operation: B/W	426.5 W
Power consumption operation: Full colour	441.7 W
Power consumption: ready	18.7 W
Power consumption: sleep	0.38 W
TEC*	0.32 kWh/week

* It is a reference value based on the ENERGY STAR Ver. 3.2 test method

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet Paper Tray

P C375

MAIN SPECIFICATIONS

OTHER OPTIONS

Cabinet, PostScript 3, Device server unit, Paperlock, Unicode Font Package for SAP, Wireless LAN (IEEE 802.11 a/b/g/n/ac)

CONSUMABLES

Toner (black)	13,500 prints
Toner (cyan/magenta/yellow)	10,000 prints
Waste toner bottle	11,000 sheets
Consumable yield measuring method	ISO/IEC 19798

For availability of models, options and software, please consult your local supplier.

Ricoh Austria GmbH
Wiedner Gürtel 11
1100 Wien
Austria

+43 5 74 264 0

www.ricoh.at

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2026 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.