

# ZU1050

Spectacular image quality, low maintenance and ultimate reliability

- 10,000 lumens laser WUXGA DLP projector
- 20,000 hours maintenance-free laser light source at full brightness\*\*
- Dust resistant – Independently tested, IP6X certified for total reliability
- Installation flexibility – 7x lens options including ultra short throw and dome lens



The ZU1050 offers enhanced features such as MultiColor Laser (MCL) technology and built-in edge-blending and warping. Part of the DuraCore laser line up, it combines longer-lifetime light source and an independent IP rated dust certification for ultimate peace of mind.

Delivering an astonishing 20,000 hours in full brightness mode, this projector achieves superior colour rendition through MCL technology producing visually striking lifelike images with exceptional detail.

Designed for even the most complex professional installations, the ZU1050 offers seven interchangeable lens options including an ultra short throw lens and single-projector dome lens for ultimate flexibility.

For large-scale projection or stacking, the ZU1050 features built-in edge-blending and warping. It also offers portrait and 360-degree orientation support. Additionally, an HDBaseT™ input is included to simplify cabling requirements and reduce installation complexity, saving time and reducing costs.



## Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	10000 lumens
Contrast ratio	2000000:1
ANSI contrast ratio	250
Contrast ratio - dynamic	6000:1
Contrast ratio - full on/off	1200:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3, 16:9, 16:10
Keystone correction - horizontal	20 degrees
Keystone correction - vertical	20 degrees
Has vertical auto keystone correction	False
Uniformity	90%
Screen size	Dependent on lens

## Lamp info

Light source	Laser
LASER life	20000 hours

## Optical

Throw ratio	Dependent on lens
Projection distance (m)	Dependent on lens

## Connectivity

Connections	<b>Inputs</b> 1 x HDMI, 1 x VGA (YPbPr/RGB), 1 x 3D sync, 1 x DVI-D, 1 x HDBaseT, 1 x BNC <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x 3D sync, 1 x HDMI <b>Control</b> 1 x RS232, 1 x Wired remote, 1 x USB-A service, 1 x mini USB service, 1 x RJ45
-------------	---

## General

Noise level (typical)	35dB
PC compatibility	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
2D compatibility	PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)
3D compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	True
360° operation	True
Operating conditions	5~40°C (>35°C, auto dim to 75% normal mode), 10~85%RH, non-condensing
Remote control	Wired ProAV remote
Heat dissipation	2625BTU/hour
In the box	AAA Battery, AC power cable 3M, Lens cover, VGA cable 1.8m, User manual CD, Quick start guide

## Networking

LAN - display	False
LAN - wireless networking	False
LAN - DHCP	True

## Power

Power supply	100 - 240V, 50 - 60Hz
Power consumption (standby)	0.5W
Power consumption (max)	910W

## Weight and dimensions

Net weight	23.4kg
Dimensions (W x D x H) (mm)	484 x 509 x 181

Date created: 27/02/2018 10:10:32

