

## Wind sensor Standard



| Specification                                                                     | Order No. | Packing unit | PS | EAN           |
|-----------------------------------------------------------------------------------|-----------|--------------|----|---------------|
|  | 0913 00   | 1            | 06 | 4010337913009 |

## Features

- The wind sensor enables e.g. blinds to be raised depending on the wind strength. In this way, sensitive blind slats can be protected from increasing wind.
- Recording and evaluating wind speeds.
- 8 adjustable wind strengths.
- Wind alarm is triggered 15 seconds after the set wind strength threshold is exceeded.
- Test run for function testing.
- Evaluation unit: Surface-mounted device for indoor installation in dry rooms.
- Wind transmitter: Device for outdoor installation.

## Technical data

### Wind transmitter

- Material of the transmitter and cup anemometer: Plastic (ABS), black
- Ambient temperature: -20 °C to +55 °C
- Connection cable: JY-ST-Y 2 x 0.6 mm<sup>2</sup>, length 3 m (can be extended to max. 50 m)
- Protection class: IP55

### Evaluation unit

- Wind warning range: 3.3 to 24.5 m/s, can be set to one of 8 levels
- Switching contact: Relay with zero-voltage NO contact
- Load capacity: max. 2 A
- Operating voltage: AC 230?V
- Protection class: IP20

### Dimensions

- W x H x D: 110 mm x 99 mm x 38 mm

## Scope of supply

- Mounting bracket included in the scope of supply.

---

## Dimensions in mm

|                                       |       |       |
|---------------------------------------|-------|-------|
| Cup diameter of the wind transmitter: | Ø 134 | H 160 |
|---------------------------------------|-------|-------|

---