
N 70, GAS HOB, 60 CM, BLACK
T26DS49S0





- √ FlameSelect® – Gain ultimate control of your flame.
- √ Pan Supports - continuous cast-iron pan supports for maximum stability and cooking convenience.
- √ Sword Knobs - a better feel and easier to operate, the new knob in an attractive design.
- √ Coating - black enamel coating.

Optional accessories

Z2480X0	Simmer plate
Z32SE10X0	Small pot support

Features

Technical Data

Product name/family: ..... gas hob w integrated controls
Built-in / Free-standing: ..... Built-in
Energy input: ..... Gas
Number of cooking zones: 4
Type of control setting devices: ..... sword knobs
Min. required niche size for installation (HxWxD): .. 45 x 560-562 x 480-492 mm
Width of the appliance: ..... 582 mm
Dimensions: ..... 53 x 582 x 520 mm
Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm
Net weight: ..... 11.4 kg
Gross weight: ..... 12.2 kg
Residual heat indicator: ..... without
Location of control panel: ..... Front
Basic surface material: ..... Enamel
Color of surface: ..... Black
Length electrical supply cord: ..... 100.0 cm
EAN code: 4242004203414
Gas connection rating: ..... 7500 W
Fuse protection: ..... 3 A
Voltage: ..... 220-240 V
Frequency: ..... 60; 50 Hz

4 242004 203414

N 70, GAS HOB, 60 CM, BLACK
T26DS49S0

Features

Design
- enamel surface, black
- black cast iron pan supports with protective rubber feet

Usage convenience
- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power
- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety
- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)
- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.5 KW

N 70, GAS HOB, 60 CM, BLACK
T26DS49S0

Dimensioned drawings

