

**RCD/MCB combination, 40 A, 30 mA, MCB trip characteristic: C, 2p, RCD trip characteristic: A**

**Part no.** FRBM6-C40/2/003-A  
**Catalog No.** 170792  
**Alternate Catalog No.** FRBM6-C40/2/003-A  
**EL-Nummer (Norway)** 1656056

Similar to illustration

## Delivery program

|                                                    |                |      |                                                                |
|----------------------------------------------------|----------------|------|----------------------------------------------------------------|
| Basic function                                     |                |      | Combined RCD/MCB devices                                       |
| Number of poles                                    |                |      | 2 pole                                                         |
| Tripping characteristic                            |                |      | C                                                              |
| Application                                        |                |      | Switchgear for industrial and advanced commercial applications |
| Rated current                                      | $I_n$          | A    | 40                                                             |
| Rated switching capacity according to IEC/EN 61009 |                | kA   | 6                                                              |
| Rated fault current                                | $I_{\Delta n}$ | A    | 0.03                                                           |
| Type                                               |                |      | Type A                                                         |
| Tripping                                           |                | s... | non-delayed                                                    |
| Product range                                      |                |      | FRBm6                                                          |
| Sensitivity                                        |                |      | Pulse-current sensitive                                        |
| Impulse withstand current                          |                |      | Partly surge-proof 250 A                                       |
| Contact sequence                                   |                |      |                                                                |

## Technical data

### Electrical

|                                           |                |      |                         |
|-------------------------------------------|----------------|------|-------------------------|
| Protected pole                            |                |      | 2                       |
| Rated voltage according to IEC/EN 60947-2 | $U_n$          | V AC | 240                     |
| Rated frequency                           | f              | Hz   | 50                      |
| Rated fault current                       | $I_{\Delta n}$ | mA   | 30                      |
| Sensitivity                               |                |      | Pulse-current sensitive |
| Rated current                             | $I_n$          | A    | 40                      |
| Tripping characteristic                   |                |      | C                       |
| Standards                                 |                |      | EN 45545-2; IEC 61373   |

## Design verification as per IEC/EN 61439

|                                                                                                                        |            |    |                                            |
|------------------------------------------------------------------------------------------------------------------------|------------|----|--------------------------------------------|
| Technical data for design verification                                                                                 |            |    |                                            |
| Rated operational current for specified heat dissipation                                                               | $I_n$      | A  | 40                                         |
| Heat dissipation per pole, current-dependent                                                                           | $P_{vid}$  | W  | 0                                          |
| Equipment heat dissipation, current-dependent                                                                          | $P_{vid}$  | W  | 8.2                                        |
| Static heat dissipation, non-current-dependent                                                                         | $P_{vs}$   | W  | 0                                          |
| Heat dissipation capacity                                                                                              | $P_{diss}$ | W  | 0                                          |
| Operating ambient temperature min.                                                                                     |            | °C | -25                                        |
| Operating ambient temperature max.                                                                                     |            | °C | 40                                         |
|                                                                                                                        |            |    | 0                                          |
| IEC/EN 61439 design verification                                                                                       |            |    |                                            |
| 10.2 Strength of materials and parts                                                                                   |            |    |                                            |
| 10.2.2 Corrosion resistance                                                                                            |            |    | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |            |    | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |            |    | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |            |    | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |            |    | Meets the product standard's requirements. |

|                                                          |  |                                                                                                                                  |
|----------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------|
| 10.2.5 Lifting                                           |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                 |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                      |  | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                  |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                   |  | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                   |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components   |  | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections        |  | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                 |  | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                               |  |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                 |  | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                         |  | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material |  | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                   |  | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                               |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility                      |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function                                |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 7.0

|                                                                                                                                                                                                    |                 |          |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|--|
| Circuit breakers and fuses (EG000020) / Earth leakage circuit breaker (EC000905)                                                                                                                   |                 |          |  |
| Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / MCB/RCCB combination (ecl@ss10.0.1-27-14-22-07 [AFZ810015]) |                 |          |  |
| Number of poles (total)                                                                                                                                                                            |                 | 2        |  |
| Number of protected poles                                                                                                                                                                          |                 | 2        |  |
| Rated voltage                                                                                                                                                                                      | V               | 240      |  |
| Rated insulation voltage Ui                                                                                                                                                                        | V               | 500      |  |
| Rated impulse withstand voltage Uimp                                                                                                                                                               | kV              | 4        |  |
| Rated current                                                                                                                                                                                      | A               | 40       |  |
| Rated fault current                                                                                                                                                                                | A               | 0.03     |  |
| Leakage current type                                                                                                                                                                               |                 | A        |  |
| Current limiting class                                                                                                                                                                             |                 | 3        |  |
| Rated short-circuit breaking capacity acc. EN 61009                                                                                                                                                | kA              | 6        |  |
| Rated short-circuit breaking capacity IEC 60947-2                                                                                                                                                  | kA              | 0        |  |
| Rated short-circuit breaking capacity Icn acc. EN 61009-1                                                                                                                                          | kA              | 6        |  |
| Disconnection characteristic                                                                                                                                                                       |                 |          |  |
| Surge current capacity                                                                                                                                                                             | kA              | 0.25     |  |
| Voltage type                                                                                                                                                                                       |                 | AC       |  |
| Frequency                                                                                                                                                                                          |                 | 50 Hz    |  |
| Release characteristic                                                                                                                                                                             |                 | C        |  |
| Concurrently switching N-neutral                                                                                                                                                                   |                 | No       |  |
| With interlocking device                                                                                                                                                                           |                 | No       |  |
| Over voltage category                                                                                                                                                                              |                 | 3        |  |
| Pollution degree                                                                                                                                                                                   |                 | 2        |  |
| Ambient temperature during operating                                                                                                                                                               | °C              | -25 - 40 |  |
| Width in number of modular spacings                                                                                                                                                                |                 | 2        |  |
| Built-in depth                                                                                                                                                                                     | mm              | 75.5     |  |
| Suitable for flush-mounted installation                                                                                                                                                            |                 | No       |  |
| Anti- nuisance tripping version                                                                                                                                                                    |                 | No       |  |
| Degree of protection (IP)                                                                                                                                                                          |                 | IP20     |  |
| Connectable conductor cross section solid-core                                                                                                                                                     | mm <sup>2</sup> | 1 - 25   |  |
| Connectable conductor cross section multi-wired                                                                                                                                                    | mm <sup>2</sup> | 1 - 25   |  |

Dimensions

|  |
|--|
|  |
|--|

Additional product information (links)

|                        |                                                                                                                                                                                                                                   |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product overview (Web) | <a href="http://www.eaton.eu/Europe/Electrical/ProductsServices/CircuitProtection/DigitalCircuitBreakers/index.htm">http://www.eaton.eu/Europe/Electrical/ProductsServices/CircuitProtection/DigitalCircuitBreakers/index.htm</a> |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|