



RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR



Description

The Cat.6A RJ45 patch cable **manufactured in Europe** guarantees very good characteristics for **10 Gigabit** Ethernet applications. The patch cable is composed of the Cat.7 raw cable **UC900 SS27 Cat.7 PUR** from Draka and **TM21** connectors from Hirose. Due to the **highly abrasion-resistant PUR** outer sheath, the cable is **resistant to mineral oil and ASTM oil**.

Cross section 4 x 2 x AWG27/7

Mounted anti-kink grommet

Temperature range **-35°C ~ +75°C**

General data

Category	6A (IEC)
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Connector type	TM21 red
Cable type	Draka UC900 SS27 Cat.7 PUR
Contacts	1.27 µ" gold plated
Pin assignment	1:1
Allocation	acc. TIA/EIA 568B
Type	Shielded
Anti-kink sleeve	put-on
Colour anti-kink sleeve	black
Locking lever	yes

Mechanical characteristics

Mating cycles	≥ 750
Bending radius	25 mm
Conductive shield	360° shield contact

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.



RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR

Cable construction

Raw cable	Cat.7
Cable structure	S/FTP
Cable construction	4x2
AWG-size/strands per core	27/7
Conductor Material	Copper

Cable sheath

Jacket material	PUR
Colour outer sheath	red
Outer diameter of the cable	5.9 mm
Euro class	Eca
Flame-retardant	acc. IEC60332-1
Halogen-free	acc. IEC60754-2
Low smoke	acc. IEC61034
Oil resistant	acc. EN 60811-2-1
UV resistance	acc. IEC60068-2-5
Ozone resistance	acc. EN60811-2-1

Environmental conditions

Temperature Range (Operation)	-35 – 75 °C
Temperature Range (Installation)	-5 – 50 °C

Electrical characteristics

NVP value	79 %
Impedance	100 ±5 Ω
Loop resistance	< 340 Ω/km
Resistance unbalance	< 3 %
Insulation resistance	≥ 2000 MΩ
Test voltage	1000 (V DC, 1min) core/core und core/screen

Transmission characteristics

Bandwidth	500MHz
-----------	--------

Standards, approvals, certifications

Connector	IEC 60603-7-51
Harmonised Standard	EN 50575

This datasheet was created automatically on 05-02-2020 . Technical changes reserved.

RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR

Available variants

Article no.	Title	Length
K8048PUI1	RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR, 1m	1.0 m
K8048PUI2	RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR, 2m	2.0 m
K8048PUI3	RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR, 3m	3.0 m
K8048PUI5	RJ45 Patch cable S/FTP, Cat.6A, TM21, UC900, PUR, 5m	5.0 m

