

2 Port Micro PS/2 VGA Cable KVM Switch

Product ID: SV221MICRO



This 2-port Micro KVM switch lets you take command of two PS/2-controlled computers from a single console, without sacrificing any desk space.

A space-saving and cost-effective computer management solution, the compact Micro KVM switch can be hung or tied up out of the way to free up work space, and features ultra-thin cables built on to the switch, leaving zero footprint once installed.

The Micro KVM switch draws power from connected computers and doesn't require an external power source - eliminating the need to position the switch near an available power outlet and saving the space required for a power cable.

Don't let the size fool you! This high quality Micro KVM switch delivers robust display capability with support for resolutions up to 2048x1536 (@60Hz) and supports hot plug-and-play installation for easy deployment.

Designed to ensure a seamlessly dependable operating experience, the 2-port Micro KVM switch is backed by StarTech.com's 3-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Allows control of 2 computers from 1 user console
- Perfect for integrating two different enterprise computer systems

Features

- Automatically switch between 2 computer using the hot key commands
- Dependable 3-year Warranty
- Designed to integrate into your existing IT infrastructure and requires no software to be installed
- Plug n Play support allows users to change computers without any interruptions
- Supports MS Intellimouse (Pro Version), Explorer and Optical Mouse
- Ultra compact design and thin coaxial cables increases the availability and manageability of the server or workstation environment by using only one keyboard, monitor and a mouse

Hardware	Warranty	3 Years
	Audio	No
	Cables Included	Yes
	Daisy-Chain	No
	KVM Ports	2
	Number of Monitors Supported	1
	PC Interface	PS/2
	PC Video Type	VGA
	Rack-Mountable	No
Performance	DVI Support	No
	Hot-Key Selection	No
	IP Control	No
	Maximum Analog Resolutions	2048x1536
	Maximum Number of Users	1
Connector(s)	Console Interface(s)	1 - VGA (15 pin, High Density D-Sub) Female 2 - PS/2 (6 pin, Mini-DIN) Female
	Host Connectors	2 - VGA (15 pin, High Density D-Sub) Male 4 - PS/2 (6 pin, Mini-DIN) Male
Indicators	LED Indicators	2 - CPU A/B Selection indicators
Physical Characteristics	Cable Length	6 ft [1.8 m]
	Enclosure Type	Plastic
	Product Height	1.1 in [27.6 mm]
	Product Length	3 in [75.6 mm]
	Product Weight	13.4 oz [380 g]
	Product Width	0.5 in [11.8 mm]
Packaging Information	Shipping (Package) Weight	1 lb [0.5 kg]
What's in the Box	Included in Package	1 - 2 Port Micro KVM on Cable 1 - Hot Key Reference Strip 1 - Instructional Manual

Product appearance and specifications are subject to change without notice.