



WAP-6017 Version: 1



N300 Wireless Access Point, Desktop, Controller Managed

The LevelOne WAP-6017 is a managed, single-band wireless access point, capable of a combined speed of up to 300 Mbps. The device runs on 2.4 GHz frequency, and can be used as part of a managed network when controlled by the LevelOne WAC-2000/WAC-2003 Wireless LAN Controller. A fast, easy and secure access point for a wide variety of network requirements.

Key Features

- Share your wireless network up to 300Mbps
- Compatible with IEEE 802.11b/g/n wireless standards
- Provides up to 4 SSIDs to separate network traffic and enhance security
- Multi-operation modes to suit different wireless applications
- Supports WEP, WPA and WPA2 encryption with IEEE 802.1x for high level security

Compatible With



WAC-2000
Gigabit Wireless LAN Controller



WAC-2003
Gigabit Wireless LAN Controller, Quad WAN

Specifications

System Specifications

Standards & Protocols:

IEEE 802.11b/g/n
IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.11e Wi-Fi Multimedia (WMM)
IEEE 802.3x Ethernet Flow Control
IEEE 802.11i Wi-Fi Protected Access (WPA2)
IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, Wireless Networking

Connectors and Cabling:

1*10/100 Mbps WAN Port
4*10/100 Mbps LAN Port
1*USB Port
1*DC Jack

Button/Knob:

WPS button

Power Input:

DC 12V 1.5A

Power Consumption:

<7W

Wireless

Operating Mode:

Gateway
Wireless AP
WiFi Repeater

Encryption:

WEP Encryption-64/128/152 bit
WPA/WPA2 Personal (WPA-PSK using TKIP or AES)
WPA/WPA2 Enterprise (WPA-EAP using TKIP)

Receive Sensitivity(dBm):

2.4GHz:
802.11n:Range?-68? dBm
802.11g:6Mbps: Range (-90) dBm .
802.11g:54Mbps: Range (-72) dBm .
802.11b:1Mbps: Range (-95) dBm.
802.11b:11Mbps: Range (-90) dBm. "

Channel:

Ch.1 ~ 11 USA
Ch.1 ~ 13 EU

EIRP(dBm):

2.4GHz:
11b 1~11Mbps: 28DBM
11g 54Mbps: 26DBM
11n MCS7/MCS15: 26DBM

Antenna:

2*2.4G Omni 5dBi detachable antenna

Frequency Band (GHz):

2.4 ~ 2.4835 GHz

Modulation:

OFDM = BPSK,QPSK, 16-QAM, 64-QAM; DSSS = DBPSK, DQPSK, CCK

Data Transfer Rate:

802.11n: 300 ~ 78 Mbps
802.11g: 54 ~ 6 Mbps
802.11b: 11 ~ 1 Mbps"

Features

General:

Multi-SSID: 2.4GHz, 4 SSID

Security:

SSID Broadcast On/Off

Management:

Web-Based GUI Configuration

QoS:

802.11e WMM Supported

Ease of Use:

Web-based GUI with Quick Installation Wizard

Web-based (HTTP) firmware upgrade

Performance

Number of Clients:

Maximum:40

Recommend:30

Environment

Temperature (°C):

Operating: 0°C ~ 55°C

Storage: -40°C ~ 70°C

Humidity (Non-condensing):

5%~95% Typical

Installation:

Desktop

Physical Specifications

Dimensions (W x D x H mm):

220*135*30 mm

Weight (g):

710

Approval and Compliance

EMI/EMS:

CE

Order Information

WAP-6017

Package Contents

WAP-6017