



32723515



IP44

Key switch for blinds with imprint surface-mounted, isolated input terminals with lock - differing lockings, Key can be removed in 3 positions, Berker W.1, grey/light grey matt

Technical features

Architecture

Type of control unit	Key
----------------------	-----

Functions

- with push lock function

Main electrical features

Nominal voltage	240 V
Rated voltage	240 V AC

Electric current

Switching current	10 A
-------------------	------

Materials

RAL colour	RAL 7011 - Iron grey
Colour of design line	grey/light grey
Colour	dark grey
Colour	iron grey
Material	thermoplastic
Surface appearance	matt

Dimensions

Depth	64 mm
Height	76 mm
Width	76 mm

Installation, mounting

- for screw fastening

Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- isolated input terminals for UP and DOWN
- with Wago clip-in 2-wire connection terminal for wiring
- with screw terminals

Cable

- with one entry for 2 cables and one entry for cable and tube

Equipment

- for e. g. garage doors
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

Use

- with lock - differing lockings
- Key can be removed in 3 positions

Safety

Protection index IP	IP55
- with 2 keys	

Use conditions

Operating temperature	-40 ... 30 °C
Storage/transport temperature	-50 ... 50 °C

Identification

Main design line	Berker W.1
------------------	------------

Instructions

- Pins of quick-release lock made of ZAMAK
--