



TL-D1600S

| | |
|---|---|
| Laufwerksschacht | 8 x 3.5-inch SATA 6Gb/s, 3Gb/s + 4 x 2.5-inch SATA 6Gb/s, 3Gb/s |
| Audio Alert On/Off Switch | Yes |
| Formfaktor | Tower |
| Host Schnittstelle | 4 x SFF-8088 |
| LED-Anzeigen | HDD 1-16, Status, Link, Lüfterfehler |
| LCD-Anzeige/ Taste | Yes |
| Tasten | Netzschalter |
| Abmessungen (HxBxT) | 303,84 × 369,89 × 319,8 mm |
| Gewicht (netto) | 11.59 kg |
| Max. Anzahl unterstützter HDDs/SSDs | 12 x 3,5-Zoll SATA 6Gb/s + 4 x 2,5-Zoll SATA 6Gb/s |
| Festplattentyp | 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives (for 3.5-inch tray slots only) 2.5-inch SATA solid state drives |
| Betriebstemperatur | 0 - 40 °C (32°F - 104°F) |
| Relative Luftfeuchtigkeit | 5 – 95% relative Luftfeuchtigkeit / nicht kondensierend, Feuchtkugeltemperatur: 27°C (80,6°F) |
| Netzteil | 250W PSU, 100 - 240V |
| Stromverbrauch: Betriebsmodus, typisch | 93,66 W |
| Fan Mode Switch | Yes (Auto, hoch, mittel, niedrig) |
| Lüfter | 3 x 92mm, 12VDC |
| Geräuschpegel | 25 db(A) |
| Systemwarnung | Summer |
| Kensington-Sicherheitsschloss | Yes |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.