

32713505



IP55

**Key change-over switch with imprint surface-mounted, isolated input terminals Lock - identical lockings, Key can be removed in 2 positions, Berker W.1, grey/light grey matt**

Technical features

**Architecture**

| | |
|---|---|
| Type of control unit | Key |

**Main electrical features**

| | |
|---|---|
| Nominal voltage | 240 V |
| Rated voltage | 240 V AC |

**Electric current**

| | |
|---|---|
| Switching current | 10 A |

**Materials**

| | |
|---|---|
| RAL colour | RAL 7011 - Iron grey |
| Colour of design line | grey/light grey |
| Colour | dark grey |
| Colour | iron grey |
| Material | thermoplastic |
| Surface appearance | matt |

**Dimensions**

| | |
|---|---|
| Depth | 64 mm |
| Height | 76 mm |
| Width | 76 mm |

**Installation, mounting**

- for screw fastening

**Connection**

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with screw terminals

**Cable**

- with one entry for 2 cables and one entry for cable and tube

**Equipment**

- for master-key systems
- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

**Use**

- Lock - identical lockings
- Key can be removed in 2 positions

**Safety**

| | |
|---|---|
| Protection index IP | IP55 |

- with 2 keys

### Use conditions

| | |
|---|---|
| Operating temperature | -40 … 30 °C |
| Storage/transport temperature | -50 … 50 °C |

### Identification

| | |
|---|---|
| Main design line | Berker W.1 |

### Instructions

- Pins of quick-release lock made of ZAMAK