

DELTA m-system Buzzer 230 V 50/60 Hz, 80 dB (A) Adjustable
loudness level aluminum-metallic



Model	
Type of acoustic signal	continuous tone
General technical data	
Loudness level	80 dB
Supply voltage	
Type of voltage	AC
Supply voltage / Rated value	230 V
Protection class	
Protection class IP	IP20
Appearance	
Color / of the enclosure	Aluminum metallic/silver
Product details	
Product component / Integrated / Transformer	Yes
Mechanical Design	
Height	44 mm
Mounting type	Miscellaneous

Net weight	46 g
Material / of the enclosure	plastic

Certificates

Reference code	
• acc. to DIN EN 61346-2	P

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TG9875-8AM>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TG9875-8AM>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TG9875-8AM

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

